

NOTES:

53-924-0000-70


Materials: SST. corrosion-resistant, Non Magnetic 303, per ASTM A484 and A582. Beryllium Copper per ASTM-B-196, QQ-C-530 Oxide-Noryl(tm) Per MIL-P-46129

Finish: Center Conductors and solder components shall be plated per MIL-G-45204 Type II, Class 1 over Nickel plate per QQ-N-290. Body and Body components shall be passivated per ASTM A380.

Frequency: DC-18GHz

VSWR: 1.15 to 18GHz

Insertion Loss: .05(SQRT(F(GHz)))



LTR	DESCRIPTION	DATE	APPR.	DRAWN LMW	CHECKED	USED ON	SRI CONNECTOR GAGE CO. 751 NORTH DRIVE MELBOURNE FL. 32934	
-	REL	09/02		APPR.	SCALE	53-924-0000-70	TITLE	
				UNLESS OTHERWISE SPECIFIED: 1. REMOVE ALL BURRS 2. BREAK ALL CORNERS & EDGES .005 R. MAX 3. CHAMFER 1st & LAST THREADS 45° 4. SURFACE FINISHED 32/ UNLESS OTHERWISE SPECIFIED. 5. DIAMETERS ON COMMON CENTERS TO BE CONCENTRIC WITHIN .002 T.I.R. 6. ALL DIMENSIONS ARE AFTER PLATING.			N JACK TO 2.9mm PLUG	
				DIMENSIONS ARE IN INCHES TOLERANCES			MATERIAL	SHEET 1
				DECIMALS	FRACTIONAL	ANGULAR	FINISH	
				.X ±.030 .XX ±.010 .XXX +.005	± 1/64	.X° ±1°0' .X°X' ±15'	SIZE A	
						FSCM NO. OHMO1	DWG. NO. 53-924-0000-70	