



Product: [579945](#)

PTZ, Mini-RG-59 #25, #18-2c, CMG, Siamese

Product Description

PTZ (CCTV+Power/Audio) Cable, Rated-CMG, 1-RG59 25 AWG solid bare copper with foam polyethylene, 95% bare copper braid, 1-20 AWG stranded bare copper pair with PVC insulation, Siamese with PVC jacket

Technical Specifications

Product Overview

Suitable Applications:	CCTV plus Audio, Pan and Tilt CCTV Control
------------------------	--

Physical Characteristics (Overall)

Conductor

Element	AWG	Stranding	Material	Nominal Diameter	No. of Conductors	No. of Coax
Coax(es)	25	Solid	BC - Bare Copper			1
Pair1	20	7x28	BC - Bare Copper	0.038 in	2	

Conductor Count:	3
------------------	---

Insulation

Element	Material	Nominal Diameter
Coax(es)	PE - Polyethylene (Foam)	0.085 in
Pair1	PVC - Polyvinyl Chloride	0.056 in

Table Notes:	Gas Injected
--------------	--------------

Color Chart

Number	Color
Coax Core	White
Pair1	Black & Red

Inner Shield

Element	Type	Material	Coverage [%]
Coax(es)	Braid	Bare Copper (BC)	95%
Pair1		No Shield	

Inner Jacket

Nominal Diameter
0.146 in

Outer Jacket

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.145 in x 0.332 in

Electrical Characteristics

Conductor DCR

Element	Nominal Conductor DCR	Nominal Inner Shield DCR

Coax(es)	31 Ohm/1000ft	5.6 Ohm/1000ft
Pair1		

Capacitance

Element	Nom. Capacitance Conductor to Conductor
Coax(es)	16.8 pF/ft
Pair1	

Impedance

Element	Nominal Characteristic Impedance
Coax(es)	75 Ohm

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.45 dB/100ft
5 MHz	0.9 dB/100ft
10 MHz	1.3 dB/100ft
50 MHz	3 dB/100ft
100 MHz	4.1 dB/100ft
200 MHz	6 dB/100ft
400 MHz	8.6 dB/100ft
700 MHz	11.6 dB/100ft
900 MHz	13.5 dB/100ft
1000 MHz	14.5 dB/100ft

Delay

Element	Max. Delay Skew	Nominal Delay
Coax(es)	80 ns/100m	1.27 ns/ft

Current

Element
Coax(es)
Pair1

Temperature Range

Installation Temp Range:	0°C To +75°C
UL Temp Rating:	75°C
Operating Temp Range:	-30°C To +75°C
Separation Temp Range:	0°C To +75°C

Mechanical Characteristics

Bulk Cable Weight:	27 lbs/1000ft
Max. Pull Tension:	48 lbs

Standards

NEC Articles:	Article 800
NEC/(UL) Compliance:	CM
CEC/C(UL) Compliance:	CM
RG Type:	59

Applicable Environmental and Other Programs

Environmental Space:	Indoor (Not Riser or Plenum)
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
EU Directive Compliance:	Yes
EU CE Mark:	Yes
MII Order #39 (China RoHS):	Yes