



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to DIN 72594-1

Documents

Assembly instruction MA_59V059

Material and plating

Connector parts

- Center contact
- Outer contact
- Contact spring
- Dielectric
- Crimping ferrule

Material

- Spring bronze
- Brass
- Stainless steel
- PA12-GB30 (f)
- Copper

Plating

- Gold, min. 0.8 µm, over nickel
- Nickel, 3-6 µm
- N/A
- Nickel, 2.5-5 µm

FAKRA -
HF

STRAIGHT JACK

59K13O-1M4A4

Electrical data

Impedance	50 Ω
Frequency	DC to 6 GHz
Return loss	≥ 30 dB, DC to 1 GHz ≥ 27 dB, DC to 3 GHz ≥ 20 dB, DC to 6 GHz
Insertion loss	≤ 0.1 x √f(GHz) dB
Insulation resistance	≥ 1x10 ³ MΩ
Center contact resistance	≤ 5 mΩ
Outer contact resistance	≤ 5 mΩ
Test voltage	750 V rms
Working voltage	335 V rms
Power current	≤ 1 A DC
RF-leakage	≥ 65 dB up to 1 GHz

- Limitations are possible due to the used cable type -

Mechanical data

Mating cycles	≥ 25
Engagement force	≤ 25 N
Disengagement force	≥ 2 N

Environmental data

Temperature range	-40°C to +105°C
Thermal shock	DIN 72594-2 clause 8.2
Temperature and humidity	DIN 72594-2 clause 8.3
Vibration and mechanical shock	DIN 72594-2 clause 8.1
Dry heat	DIN 72594-2 clause 8.4
RoHS (f)	compliant

- Limitations are possible due to the used cable type -

Tooling

Crimping tool	11W150-000
Crimp insert outer contact	11W150-104
Crimping tool - Incl. Crimp insert center contact	11W161-8M4

Suitable cables

Cable type	RTK 031
------------	---------

Packing

Standard	10 / 500 / 5.000 / 20.000 pcs in box
Weight	2.0 g/pce

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF_35/09.14/6.2