



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to IEC 60169-10, CECC 22130, US MIL-C-39012

Documents

N/A

Material and plating

Connector parts

- Center contact
- Outer contact
- Body
- Dielectric
- Substrate

Material

- Beryllium copper
- Beryllium copper
- Brass
- PTFE
- Al₂O₃

Plating

- Gold, min. 1.27 µm, over nickel
- Gold, min. 0.8 µm, over nickel
- Gold, 0.15 µm

Electrical data

Impedance	50 Ω
Frequency	DC to 2 GHz
Return loss	≥ 24.9 dB, DC to 1 GHz ≥ 20.8 dB, 1 GHz to 2 GHz
Center contact resistance	≤ 5 mΩ
Outer contact resistance	≤ 2.5 mΩ
Contact current	1.5 A DC typ.
Power handling	1 W at 25°C derated linearity to 0 Watts at 125°C

Mechanical data

Mating cycles	≥ 500
Center contact captivation: axial	≥ 10 N
Engagement force	≤ 63 N
Disengagement force	8 N min. to 63 N max.

Environmental data

Temperature range	-55°C to +155°C
-------------------	-----------------

Tooling

N/A

Suitable cables

N/A

Packing

Standard	100 pcs in bag
Weight	1.9 g/pce

RF_35/12.04/3.0

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Kerstin Herzog	25/07/05	Frank Weiß	05/08/05	a00	04-0130	Siegmar Hoyer	01/08/05
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de				Tel.: +49 8684 18-0 Fax: +49 8684 18-499 email: info@rosenberger.de			Page 2 / 2