



All dimensions are in mm; tolerances according to ISO 2768 m-H
 Y = Part number has to be accomplished by codification

Interface

According to DIN 72594-1, USCAR 17

Documents

Assembly instruction MA_59V056

Material and plating

Connector parts

- Center contact
- Outer contact
- Dielectric
- Crimping ferrule
- Lock washer
- Housing

Material

- Spring bronze
- Brass
- PA 12
- Copper
- Steel
- PBT

Plating

- Gold, min. 0.8 µm, over chemical nickel
- Nickel, 3-6 µm
- Nickel, 2.5-5 µm

Electrical data

Impedance	50 Ω *
Frequency	DC to 1 GHz
Return loss	≥ N/A
Insertion loss	≤ 0.1 x √f(GHz) dB
Insulation resistance	≥ 1x10 ³ MΩ
Center contact resistance	≤ 5 mΩ
Outer contact resistance	≤ 5 mΩ
Test voltage	750 V rms
Working voltage	335 V rms
Power current	≤ 1 A DC
RF-leakage	≥ 65 dB up to 1 GHz

- Limitations are possible due to the used cable type - * Interface only

Mechanical data

Mating cycles	≥ 25
Engagement force	≤ 25 N
Disengagement force	≥ 2 N
Retention force latch	≥ 110 N
Retention force primary lock	≥ 110 N
Coding efficiency	≥ 40 N

Environmental data

Temperature range	-40°C to +105°C
Thermal shock	DIN 72594-2 clause 6.2
Temperature and humidity	DIN 72594-2 clause 6.3
Vibration and mechanical shock	DIN 72594-2 clause 6.1
Dry heat	DIN 72594-2 clause 6.4
2002/95/EC (RoHS)	compliant

- Limitations are possible due the used cable type -

Tooling

Crimping tool	11W150-000
Crimp insert outer contact	11W150-109
Crimping tool -	
Incl. Crimp insert center contact RG59	11W161-800
Crimping tool -	
Incl. Crimp insert center contact RG62	11W161-809

Suitable cables

Cable type	RG 62 CommScope RG 59 CommScope
------------	------------------------------------

Packing

Standard	500, 5000, 20000 pcs in box
Weight	4.26 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Denis Oberhöller	20/04/06	Höfling	10.07.09	f00	09-0461	M. Singhammer	06/07/09
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de				Tel.: +49 8684 18-0 Fax: +49 8684 18-499 email: info@rosenberger.de			Page 2 / 2