



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to ISO 20860-1

Documents

PCB layout MB_355; MB_172
Tape & reel packaging VG273.56000

Material and plating

Connector parts

| | |
|----------------|------------|
| Center contact | Brass |
| Outer contact | Zinc alloy |
| Dielectric | HTN |
| Housing | HTN |

Plating

AuroDur®, gold plated
Tin, 2-5 µm, over Nickel 1-5 µm

Electrical data

| | |
|---------------------------|--|
| Impedance | 50 Ω |
| Frequency | DC to 6 GHz |
| Return loss | ≥ 26 dB (DC to 1 GHz) ≥ 23 dB (DC 1 to 2.4 GHz) ≥ 20 dB (DC 2.4 to 4 GHz) ≥ 15 dB (DC 4 to 6 GHz) |
| Insertion loss | ≤ 0.15 x dB |
| Insulation resistance | ≥ 1x10 ³ MΩ |
| Center contact resistance | ≤ 5 mΩ |
| Outer contact resistance | ≤ 5 mΩ |
| Test voltage | 750 V rms |
| Working voltage | 335 V rms |
| Power current | ≤ 1 A DC |

- Connector only, VSWR in application depends decisive on PCB layout –

Mechanical data

| | |
|-----------------------|---------|
| Mating cycles | ≥ 25 |
| Engagement force | ≤ 25 N |
| Disengagement force | ≥ 2 N |
| Retention force latch | ≥ 110 N |
| Coding efficiency | ≥ 40 N |

Environmental data

| | |
|--------------------------------|---------------------------------|
| Temperature range | -40°C to +125°C |
| Thermal shock | DIN 72594-2 clause 8.2 |
| Temperature and humidity | DIN 72594-2 clause 8.3 |
| Vibration and mechanical shock | DIN 72594-2 clause 8.1 |
| Dry heat | DIN 72594-2 clause 8.4 |
| Resistance to soldering heat | acc. IEC 60068-2-58 Group 3 & 4 |
| RoHS | compliant |

*Only valid for the connector itself. Depending on cable side.

Tooling

N/A

Packing

| | |
|----------|------------------------|
| Standard | 560 pcs in tape & reel |
| Weight | 2.4 g |

Storage condition

| | |
|----------------------------|---|
| Moisture Sensitivity Level | 2 |
|----------------------------|---|

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF_35/05.10/6.2