



All dimensions are in mm; tolerances according to ISO 2768 m-H

**Interface**

According to ISO 20860-1

**Documents**

PCB layout MB\_355; MB\_172  
Tape & reel packaging VG273.56000

**Material and plating**

**Connector parts**

Center contact  
Outer contact  
Dielectric  
Housing

**Material**

Brass  
Zinc alloy  
HTN  
HTN

**Plating**

AuroDur®, gold plated  
Tin, 2-5 µm, over Nickel 1-5 µm

**Electrical data**

Impedance	50 Ω
Frequency	DC to 6 GHz
Return loss	≥ 26 dB (DC to 1 GHz) ≥ 23 dB (DC 1 to 2.4 GHz) ≥ 20 dB (DC 2.4 to 4 GHz) ≥ 15 dB (DC 4 to 6 GHz)
Insertion loss	≤ 0.15 x dB
Insulation resistance	≥ 1x10 <sup>3</sup> MΩ
Center contact resistance	≤ 5 mΩ
Outer contact resistance	≤ 5 mΩ
Test voltage	750 V rms
Working voltage	335 V rms
Power current	≤ 1 A DC

- Connector only, VSWR in application depends decisive on PCB layout –

**Mechanical data**

Mating cycles	≥ 25
Engagement force	≤ 25 N
Disengagement force	≥ 2 N
Retention force latch	≥ 110 N
Coding efficiency	≥ 40 N

**Environmental data**

Temperature range	-40°C to +125°C
Thermal shock	DIN 72594-2 clause 8.2
Temperature and humidity	DIN 72594-2 clause 8.3
Vibration and mechanical shock	DIN 72594-2 clause 8.1
Dry heat	DIN 72594-2 clause 8.4
Resistance to soldering heat	acc. IEC 60068-2-58 Group 3 & 4
RoHS	compliant

\*Only valid for the connector itself. Depending on cable side.

**Tooling**

N/A

**Packing**

Standard	560 pcs in tape & reel
Weight	2.4 g

**Storage condition**

Moisture Sensitivity Level	2
----------------------------	---

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF\_35/05.10/6.2