

All dimensions are in mm
 Y = Part number has to be accomplished by codification

Interface and coding

According to
 Clip slot suitable for

DIN 72594-1, USCAR 17
 ZUH-360 (13257300)

Material and plating

Connector parts
 Housing

Material
 PBT-GF23



Mechanical data

Mating cycles ≥ 25
 Retention force latch ≥ 110 N
 Retention force primary lock ≥ 110 N
 Coding efficiency ≥ 40 N

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF_35/09.14/6.2

Environmental data

Temperature range -40°C to +105°C
 Thermal shock DIN 72594-2 clause 8.2
 Temperature and humidity DIN 72594-2 clause 8.3
 Vibration and mechanical shock DIN 72594-2 clause 8.1
 Dry heat DIN 72594-2 clause 8.4
 RoHS compliant



Application

Applicable e.g. for following connectors: 59K13O-1xx*; 59K16A-1xx*; 59K16B-1xx*; 59K17O-1xx*; 59K17K-1xx*














* -xx for all available cable variations

Packing

Standard 250 pcs in box
 Weight 2.81 g/pce

Coding

Part Number has to be accomplished by codification

Coding	Color	RAL	Part-Number
 A	Jet Black	sim. 9005	59Z067-C00-A
 B	Cream	sim. 9001	59Z067-C00-B
 C	Signal Blue	sim. 5005	59Z067-C00-C
 D	Claret Violet	sim. 4004	59Z067-C00-D
 E	Leaf Green	sim. 6002	59Z067-C00-E
 F	Nut Brown	sim. 8011	59Z067-C00-F
 G	Blue Grey	sim. 7031	59Z067-C00-G
 H	Heather Violet	sim. 4003	59Z067-C00-H
 I	Beige	sim. 1001	59Z067-C00-I
 K	Curry	sim. 1027	59Z067-C00-K
 L	Carmine Red	sim. 3002	59Z067-C00-L
 M	Pastel Orange	sim. 2003	59Z067-C00-M
 N	Pastel Green	sim. 6019	59Z067-C00-N
 Z	Water Blue	sim. 5021	59Z067-C00-Z

1) on request



Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF_35/09.14/6.2