



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to DIN 72594-1

Material

Housing PBT-GF20 (d)
Secondary Lock PBT-GF10

Mechanical data

Mating cycles ≥ 25
Retention force latch $\geq 110\text{ N}$
Retention force primary lock $\geq 80\text{ N}$
Retention force secondary lock $\geq 60\text{ N}$
Coding efficiency $\geq 40\text{ N}$

Environmental data

Temperature range -40°C to +105°C
Thermal shock DIN 72594-2 clause 8.2
Temperature and humidity DIN 72594-2 clause 8.3 (b)
Vibration and mechanical shock DIN 72594-2 clause 8.1 (b)
Dry heat DIN 72594-2 clause 8.4 (b)
RoHS compliant (b)

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG RF_35/05.10/6.2

Application

Applicable e.g. for following connectors: 59K13O-1xx^{*1)}, 59K13D-1xx^{*1)}, 59K13F-1xx^{*1)}, 59K16A-1xx^{*1)}, 59K16B-1xx^{*1)}
^{*1)} -xx for all available cable variations

Packing

Standard 500 pcs in box, 1500 pcs in reusable container (d)
 Weight 1.48 g/pce

Coding

Part Number has to be accomplished by codification

Coding	Color	RAL	Part-Number
A	black	sim. 9005	59Z113-000-A
B	white	sim. 9001	59Z113-000-B
C	blue	sim. 5005	59Z113-000-C
D	bordeauxviolet	sim. 4004	59Z113-000-D
E	green	sim. 6002	59Z113-000-E
F	brown	sim. 8011	59Z113-000-F
G	grey	sim. 7031	59Z113-000-G
H	violet	sim. 4003	59Z113-000-H
I	beige	sim. 1001	59Z113-000-I
K	curry	sim. 1027	59Z113-000-K
L	carmine red	sim. 3002	59Z113-000-L ^{*2)}
M	pastel orange	sim. 2003	59Z113-000-M ^{*2)}
N	pastel green	sim. 6019	59Z113-000-N ^{*2)}
Z	waterblue	sim. 5021	59Z113-000-Z
	traffic purple	sim. 4006	secondary lock

^{*2)} on request