



Pre-set at factory to desired value within a +/- 4% tolerance. When preset torque value is achieved, a distinct click is felt and heard, followed by a sudden release into several degrees of free movement. Ideal for applications in which one torque value is used extensively. Compact design makes these tools invaluable in hard to reach locations. Tools automatically reset when torquing- force is removed.

**Material and plating**

**Connector parts**

	Material	Plating
Handel	Stainless steel	n. a.
Head 32mm	Stainless steel	n. a.

**Mechanical data**

Wrench size	32 mm
Torque setting	220 in. lbs 25 N/m

**Packing**

Standard	1 pce
Weight	300 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Chr. Entsfellner	29.11.11	Rong Fang	28.02.13	a00	13-0005	S. Peteranderl	28.02.13
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany <a href="http://www.rosenberger.de">www.rosenberger.de</a>				Tel.: +49 8684 18-0 Fax: +49 8684 18-499 email: <a href="mailto:info@rosenberger.de">info@rosenberger.de</a>			Page 1 / 1