# 70-725-1

Socket, SE Relays, 30A, 6 pins, screw connectors, separate contact, for 725 power relay



#### Main

Complementary

Rated Current	30 A	
[Ue] rated operational voltage	300 V	
Connections Terminals	Screw terminalsolid Screw terminalstranded	
Tightening Torque	Screw 1.2 N.m	
Fixing Mode	Clip-on 35 mm symmetrical DIN rail	
Product Weight	2.36 oz (67 g)	
Depth	2.78 in (70.5 mm)	

#### Environment

Flame Retardance	UL94-V0

## Ordering and shipping details

GTIN	3606480277986	
Nbr. of units in pkg.	1	
Package weight(Lbs)	2.36 oz (67.0 g)	

### **Packing Units**

Unit Type of Package 1	PCE
Package 1 Height	2.79 in (7.08 cm)
Package 1 width	2.13 in (5.4 cm)
Package 1 Length	0.93 in (2.35 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	23.63 oz (670.0 g)
Package 2 Height	2.99 in (7.6 cm)
Package 2 width	4.37 in (11.1 cm)
Package 2 Length	4.88 in (12.4 cm)
Unit Type of Package 3	CAR
Number of Units in Package 3	200
Package 3 Weight	29.54 lb(US) (13.4 kg)
Package 3 Height	10.83 in (27.5 cm)

Package 3 width	9.33 in (23.7 cm)
Package 3 Length	15.94 in (40.5 cm)

## **Dimensions**

