

## LPS250 Series

250 Watts

### Data Sheet

**Total Power:** 250 Watts  
**Input Voltage:** 85 - 264 Vac  
 120 - 300 Vdc  
**# of Outputs:** Single

### SPECIAL FEATURES

- Active power factor correction
- IEC EN6100-3-2 compliance
- Remote sense & remote inhibit
- Power fail
- Single wire current sharing
- Built-in EMI filter
- 2:1 Wide range output voltage adjust
- 2 Supervisory outputs 5 V and 12 V
- Overvoltage protection
- Overload protection
- Thermal overload protection
- DC power good
- 120 kHz switching frequency
- RoHS compliant
- Cover -C
- Optional top with fan cover -CF
- Optional end fan cover -CEF

### SAFETY

- VDE 62368
- UL 62368
- CSA 62368
- NEMKO 62368
- CB Certificate and report 2186
- CE Mark (LVD)



### Electrical Specifications

#### Input

Input range	85 - 264 Vac; 120 - 300 Vdc
Frequency	47 - 440 Hz
Inrush current	20 A max, cold start @ 25 °C
Efficiency	75% typical at full load
EMI filter	FCC Class B conducted and radiated CISPR 22 Class B conducted and radiated EN55022 Class B conducted and radiated VDE 0878 PT3 Class B conducted and radiated
Safety ground leakage current	< 0.5 mA @ 50/60 Hz, 264 Vac input

#### Output

Maximum power	With cover: 250 W with 30 CFM forced air. (-C) (-CF) (CEF)
Supervisory output	5 V @ 100 mA regulated; 12 V @ 500 mA
Adjustment range	2:1 wide ratio
Hold-up time	20 ms @ 250 W load, 115 VAC nominal line
Overload protection	Short circuit protection on all outputs. Case overload protected @ 10 - 145% above peak rating
Overvoltage protection	5 V output: 5.7 to 6.7 Vdc. Other models 10% to 25% above nominal output

#### Logical Control

Power failure	TTL Logic signal goes high 50 - 150 msec after 5 V output. It goes low at least 4 ms before loss of regulation
Remote on/off	Requires an external contact (N.O or N.C) to inhibit outputs
DC - OK	TTL logic goes high 50 - 150 msec after the output. It goes low when there is loss of regulation.
Remote sense	Compensates for 0.5 V lead drop minimum, will operate without remote sense connected. Reverse connection protected

## Environmental Specifications

<b>Operating temperature</b>	0° to 50 °C ambient; derate each output at 2.5% per degree from 50° to 70 °C
<b>Storage temperature</b>	-40 °C to +85 °C
<b>Temperature coefficient</b>	± 0.4% per °C
<b>Electromagnetic susceptibility</b>	Designed to meet IEC 801, -2, -3, -4, -5, -6, Level 3
<b>Humidity</b>	Operating; non-condensing 5% to 95%
<b>Vibration</b>	Three orthogonal axes, sweep at 1 oct/min, 5 min. dwell at four major resonances 0.7 G peak 5 Hz to 500 Hz, operational
<b>MTBF demonstrated</b>	> 550,000 hours at full load and 25 °C ambient conditions

## Ordering Information

Model Number	Output Voltage	Minimum Load	Maximum Load with 30CFM Forced Air	Peak Load <sup>1</sup>	Regulation <sup>2</sup>	Ripple P/P (PARD) <sup>3</sup>
LPS252-C	5 V (3 - 6 V)	1.50 A	50 A	60 A	±2%	50 mV
LPS253-C	12 V (6 - 12 V)	0.63 A	21 A	25 A	±2%	120 mV
LPS254-C	15 (12 - 24 V)	0.50 A	16.7 A	20 A	±2%	150 mV
LPS255-C	24 V (24 - 48 V)	0.32 A	10.4 A	12.5 A	±2%	240 mV

1. Peak current lasting < 30 seconds with a maximum 10% duty cycle.
2. At 25 °C including initial tolerance, line voltage, load currents and output voltages adjusted to factory settings.
3. Peak-to-peak with 20 MHz bandwidth and 10 µF in parallel with a 0.1 µF capacitor at rated line voltage and load ranges.
4. If optional CF or CEF fans are not used, 30CFM forced air cooling needs to be provided and is required through the length of the power supply. Not convection rated.
5. Output voltage adjustment requires a minimum load.
6. Remote inhibit resets OVP latch
7. This product is a Component Power Supply and is only for inclusion by professional installers within other equipment and must not be operated as a standalone product. EMC compliance to appropriate standards must be verified at the system level. This product is for sale to OEMs and System Integrators, including through Distribution Channels. It is not intended for sale to End Users.

**Note:** -CF suffix added to the model number indicates cover with top fan. -CEF suffix added to the model number indicates cover with dual end mounted fan cover and AC inlet.