# therein, as well as the proprietary and novel features of the subject matter, are reserved by Rosenberger North America and are disclosed in confidence. They are not to be manufactured, used, sold or disclosed to others, nor are devices embodying such features or information derived from these disclosures to be used or disclosed, unless and until expressly authorized by Rosenberger North America, These drawings, specifications, processes, etc., are and remain the property of Rosenberger North America, and are not to be copied or reproduced without permission.

# **Technical Data Sheet**

# Rosenberger

Cable assembly SMA / WSMP – RTK-Flex047

70W-32K1-W1K2-XXXXX



All dimensions are in mm; tolerances:

 $\leq$  100: XXX ± 2.0; > 100 to  $\leq$  1500: XXX ± 5.0; > 1500 to  $\leq$  3000: XXX ± 10.0; > 3000: ± 1.5%

# **Available variants**

Туре	Max Insertion Loss	Marking	Weight (g) / pce
70W-32K1-W1K2-XXXXX	≤0.0059 dB/mm * A mm + 0.64 dB	ROSENBERGER YYWW 70W-32K1-W1K2-XXXXX	0.0052 g/mm * A mm +2.17 g

XXXXX - length in mm = A

WW – week

YY – year

Note: max Insertion Loss:

First Constant = Cable attenuation in dB/mm; Second Constant = Connector left and Connector right

Weight

First Constant = Cable weight per mm; Second Constant = Connector left and Connector right per pce

# Assembly parts

Connector left SMA Jack 32K10D-270L5
Connector right WSMP Jack W1K203-270D3
Cable RTK-Flex047

## **Electrical data**

Impedance 50 Ω

Frequency DC to 18 GHz

Return Loss<sup>1</sup>  $\geq$  20.5 dB, DC to 18 GHz see table available variants

### **Mechanical data**

Minimum bend radius:

Single 5 mm Multiple 10 mm

### **Environmental data**

Temperature range -40°C to +125°C compliant

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Lizzy Beller	01/08/20	Mark Bennett	01/20/20	100	Preliminary	Mark Bennett	01/20/20
Rosenberger North America P.O. Box 309 Akron, PA USA 17501					: +1.717.859.8900 : +1.717.859.7044		Page
www.rosenbergerna.com				Ema	il: info@rosenbergerna.con	<u>n</u>	1/1

<sup>&</sup>lt;sup>1</sup> Return Loss and Insertion Loss includes the measurement adaptor