



SEC. A-A

RUBBER PART GENERAL TOLERANCE			
PART DIM.	1	2	③
0 TO 3	± 0.2	± 0.3	± 0.4
3 TO 6	± 0.2	± 0.4	± 0.5
6 TO 10	± 0.3	± 0.5	± 0.6
10 TO 18	± 0.3	± 0.6	± 0.8
18 TO 30	± 0.4	± 0.8	± 1.0
30 TO 50	± 0.5	± 1.0	± 1.5
50 TO 80	± 0.6	± 1.2	± 2.0
80 TO 120	± 0.7	± 1.4	± 2.5
120 TO 180	± 0.8	± 1.6	± 3.0
180 TO 250	± 1.0	± 2.0	± 4.0
250 TO 315	± 1.2	± 2.5	± 5.0
315 TO 400	± 1.5	± 3.0	± 6.0
400 TO 500	± 1.8	± 3.5	± 7.0
500 OVER	± 0.4 %	± 0.8 %	± 1.5 %

注記

1.材料 NBR

色 : 青

NOTE

1.MATERIAL : NBR

COLOR : BLUE

ISSUE MARK

								CUSTOMER				MATERIAL SPEC. SEE NOTE			TREAT. & FIN.							
								CUSTOMER PART NO.				CUSTOMER DWG NO.										
96.10.14		NEW		C96-M889		M.T		OFFICE				TRIAL PART NO.			NAME 090 RUBBER STOPPER							
LET	DATE	REVISION RECORD		NO.		CHKD		VENDOR				VENDOR NO.			(USE FOR 4.40 DIA CAVITY)							
GENERAL TOLERANCE								DWG TYPE				DWG SOURCE			DWG DATE		UNIT		SCL		ANGLE	
	10MAX	50MAX	100MAX	250MAX	250OVR	ANGLE	ECCENT	R	NEW		96.10.14		mm		10/1		3		PART NO. 7157-3649			
A	±0.15	±0.2	±0.3	±0.5	±0.75	±30'	0.1	APPROVED		CHECKED		CHECKED		DESIGN		DRAWN		CH.CODE 7157-3649: R				
B	±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	TAKAOKA		TSUJI		TAKAOKA						DWG NO. 7157-3649: R				
③	±0.3	±0.5	±0.8	±1.4	±2	±30'	0.15	76.10.18		96.10.17		85.01.11		96.10.14				YAZAKI CORPORATION				
SPECIFIED RUBBER PART GENERAL TOLERANCE 3						MASS																