



Product: <u>734A1P</u> ☑

DS3/DS4 Central Office Coax, RG-59, 20 AWG Solid BC, Foil + 85% TC Braid, Flamarrest® Jkt, CMP

Product Description

DS3/DS4 Central Office Coax, RG-59, 20 AWG Solid Bare Copper Conductor, FEP Insulation, Foil + 85% Tinned Copper Braid Shield, Flamarrest® Jacket,

Technical Specifications

| Produc | Product Overview | | | | |
|---|----------------------|-------------------------|--|-----------------|--|
| Suitable Applications: Central office | | tral office wiring, DS3 | 3/DS4 interconnect, 734/735 telecommunications systems, switchboard communications | | |
| Constru | Construction Details | | | | |
| RG Type: | : | 59 | | | |
| Conducto | or | | | | |
| Size | Stranding | Nom. Diamete | r Material | | |
| 20 AWG | Solid | 0.032 in | BC - Bare Copper | | |
| Insulation | nsulation | | | | |
| | Ma | terial | Nom. Insul | lation Diameter | |
| FEP - Fluorinated Ethylene Propylene (Foam) | | (Foam) 0.148 in (3. | .76 mm) | | |

Outer Shield

| Layer | Outer Shield Type | Material | Material Trade Name | Coverage | |
|-------|-------------------|-------------------------|---------------------|----------|--|
| 1 | Таре | Bi-Laminate (Alum+Poly) | Beldfoil® | 100% | |
| 2 | Braid | Tinned Copper (TC) | | 85% | |

Outer Jacket

| Material | Nom. Diameter | | |
|--------------------------|--------------------|--|--|
| PVC - Polyvinyl Chloride | 0.213 in (5.41 mm) | | |

Electrical Characteristics

Return Loss (RL)

| Frequency | Min. Return Loss | | |
|-------------|------------------|--|--|
| 15 - 95 MHz | 30 dB | | |

Electricals

| Nom. Conductor DCR | Nom. Outer Shield DCR | Nom. Capacitance Cond-to-Shield | Nom. Characteristic Impedance | Nom. Velocity of Prop. |
|-------------------------------|-----------------------------|---------------------------------|-------------------------------|------------------------|
| 10.1 Ohm/1000ft (33.1 Ohm/km) | 2.4 Ohm/1000ft (7.9 Ohm/km) | 17.3 pF/ft (56.8 pF/m) | 75 Ohm | 80% |

Voltage

UL Voltage Rating 300 V (CMP)

Mechanical Characteristics

Temperature

UL Temperature Operating

60°C 0°C to +75°C

Bend Radius



| Max. Pull Tension: | 49 lbs (22 kg) | ĺ |
|--------------------|----------------|---|
| Bulk Cable Weight: | 35 lbs/1000ft | l |

Standards and Compliance

| Environmental Suitability: | Indoor - Plenum, Indoor |
|----------------------------------|--|
| Sustainability: | CA Prop 65 |
| Flammability / Reaction to Fire: | NFPA 262 |
| NEC / UL Compliance: | CMP |
| CEC / C(UL) Compliance: | CMP |
| European Directive Compliance: | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| APAC Compliance: | China RoHS II (GB/T 26572-2011) |
| Non-Plenum Number: | 734A1 |

History

| Update and Revision: | Revision Number: 0.324 Revision Date: 12-15-2021 |
|----------------------|--|

Variants

| Item # | Color | Putup Type | Length | UPC |
|----------------|-------|------------|----------|--------------|
| 734A1P 008500 | Gray | Reel | 500 ft | 612825184188 |
| 734A1P 0081000 | Gray | Reel | 1,000 ft | 612825184157 |

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.