


REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	04/15/11	J.S.




NOTES:

MATERIALS:

1. BODY = STAINLESS STEEL PER ASTM A582, ALLOY 303, CONDITION "A".
2. INSULATOR = VIRGIN WHITE TEFLON PER ASTM D1710, GRADE 1, TYPE I, CLASS "B".
3. CONTACT = BERYLLIUM COPPER PER ASTM B196, ALLOY C17300, TEMPER TD04.

FINISHES:

1. BODY = GOLD PLATE PER MIL-G-45204, TYPE II, CLASS 0, GRADE C, OVER .000050 TO .00010 STRESS FREE NICKEL PER QQ-N-290.
2. CONTACT = GOLD PLATE PER MIL-G-45204, TYPE II, CLASS 1, GRADE C, OVER .00010 TO .00020 STRESS FREE SULFAMATE NICKEL PER QQ-N-290.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON	DWN: J.S.	DATE 04/15/11	 Property of Radial This document cannot be reproduced or communicated to a third party without prior written permission of RADIALL.				
	CHKD: D.N.	DATE 04/15/11				SSMB STRAIGHT MALE JACK (2) HOLE FLANGE MOUNT SOLDER POT RECEPTACLE	
DECIMAL	ANGLE	APVD: J.M.	DATE 04/15/11	SIZE A	FSCM NO. 19505		
REFERENCE:	MATERIALS & FINISHES: SEE NOTES		SCALE 7:1	THIRD ANGLE PROJECTION	SHEET 1 OF 1		
ORIGINATED: J.S. DATE: 04/15/11							

7499-1513-000