


NOTES:

1. FOR USE WITH BOEING BMS 13-65 OG & ADAMS RUSSELL FC20Z CABLES
2. FOR CABLING INSTRUCTIONS SEE 3-546-1.
3. FOR CRIMPING USE DIE KTH-2216.
4. INTERFACE PER MIL-STD-348, FIG. 301-1.
5. CENTER CONTACT (1-569-35MA9) SUPPLIED UNASSEMBLED.
6. MARK PACKAGE: HS5939-1 (DATE CODE)
755-93-7 (DATE CODE)
91836 (DATE CODE)
7. MATERIALS:
INSULATOR: TEFLON, ASTM D1710
K-GRIP SLEEVE: COM. BRONZE, ASTM B135
GASKET: SILICONE RUBBER, A-A-59588
OUTER CONTACT } BER. COPPER, ASTM B196
SPRING WASHER }
ALL OTHER METAL PARTS: BRASS, ASTM B16
8. FINISHES:
CENTER CONTACT: .000050 MIN GOLD PLATE, PER ASTM B488 OVER
.000050 MIN. NICKEL PER AMS-QQ-N-290 (RoHS)
SPRING WASHER: .00020 MIN SILVER PLATE PER ASTM B700 OVER
.000020 MIN NICKEL PER AMS-QQ-N-290 (RoHS)
ALL OTHER METAL PARTS: .000050 MIN NICKEL PER AMS-QQ-N-290
OVER .000050 MIN COPPER PER ASTM B734 (RoHS)

9. ELECTRICAL CHARACTERISTICS:
NOMINAL IMPEDANCE: 50 OHMS
WORKING VOLTAGE: 500 VRMS
FREQUENCY RANGE: DC TO 4 GHz.
VSWR: 1.30 MAX. 0-4 GHz
INSERTION LOSS: .2 dB MAX. AT 3 GHz
10. CONNECTOR WEIGHT: 10.2 GRAMS

REVISIONS	
ISSUE	CHANGES
0	ER 37066 AR 07/18/96
1	CN 38710 C DCT 6/23/3
2	CN 39740 C PMC 12/20/06
D	REVISED PER DMF304 & ER040644 KPL 02/03/12
CUSTOMER SALES DRAWING	
<small>THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.</small>	
SCALE	4:1
APPROX SURFACE AREA	
CAGE CODE:	91836
REF:	
PLUG, BNC	
DRAWN AR	DATE 07/18/96
DESIGN AR	DATE 07/18/96
APPR.	DATE
 Winchester Electronics Corporation 62 Barnes Industrial Road North Wallingford, Connecticut 06492	
755-93-7	

755-93-7