


Product: [7809R](#) 

RF 300 Wireless Coax, #13, CMR/CMG



## Product Description

Intermediate type, RF 300, 13 AWG solid .072" bare copper conductor, gas-injected foam HDPE insulation, Duobond® II, tinned copper braid shield (95% coverage), PVC jacket.

## Technical Specifications

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Coax
13	Solid	BC - Bare Copper	0.072 in	1

Conductor Count:	1
------------------	---

#### Insulation

Material	Nominal Diameter
PE - Polyethylene (Foam)	0.19 in

Table Notes:	Gas Injected
--------------	--------------

#### Outer Shield

Type	Layer	Material	Material Trade Name	Coverage [%]
Tape	1	Tri-Laminate (Alum+Poly+Alum)	Duofoil®	100%
Braid	2	Tinned Copper (TC)		95%

#### Outer Jacket

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.3 in

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR	Nominal Conductor DCR	Conductor Resistance	Nominal Outer Shield DCR	Outer Conductor DCR
2.1 Ohm/1000ft	2.1 Ohm/1000ft		2.4 Ohm/1000ft	2.4 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Shield
23 pF/ft

#### Inductance

Nominal Inductance
0.06 µH/ft

#### Impedance

Nominal Characteristic Impedance
50 Ohm

#### High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss

5 MHz	0.45 dB/100ft
10 MHz	0.6 dB/100ft
30 MHz	1 dB/100ft
50 MHz	1.3 dB/100ft
150 MHz	2.2 dB/100ft
220 MHz	2.7 dB/100ft
450 MHz	3.9 dB/100ft
900 MHz	5.6 dB/100ft
1500 MHz	7.3 dB/100ft
1800 MHz	8.1 dB/100ft
2000 MHz	8.6 dB/100ft
2500 MHz	9.7 dB/100ft
3000 MHz	10.8 dB/100ft
3500 MHz	11.8 dB/100ft
4500 MHz	13.5 dB/100ft
5800 MHz	15.8 dB/100ft
6000 MHz	16 dB/100ft

#### Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.17 ns/ft	86%

#### Power Rating

Frequency [MHz]	Max. Power Rating [W]	Nominal Power Rating [W]
30 MHz	2,161 W	2,161 W
50 MHz	1,658 W	1,658 W
150 MHz	928 W	928 W
220 MHz	758 W	758 W
450 MHz	522 W	522 W
900 MHz	367 W	367 W
1,500 MHz	278 W	522 W
2,000 MHz	239 W	253 W
2,500 MHz	212 W	239 W
3,500 MHz	179 W	212 W
4,500 MHz	157 W	194 W
6,000 MHz	135 W	179 W
4,500 MHz	157 W	157 W
5,800 MHz	137 W	137 W
6,000 MHz	135 W	135 W

#### Voltage

UL Voltage Rating
300 V RMS

#### VSWR

Frequency [MHz]	Max. VSWR
5-6000 MHz	1.25:1

#### Temperature Range

UL Temp Rating:	60°C
Operating Temp Range:	-40°C To +75°C

#### Mechanical Characteristics

Bulk Cable Weight:	61 lbs/1000ft
Max. Pull Tension:	135 lbs
Min. Bend Radius/Minor Axis:	3 in

#### Standards

NEC/(UL) Compliance:	CMR
CEC/C(UL) Compliance:	CMG
CPR Euroclass:	Eca