

View on mating side

○	A	A	A	A	A	A	A	A	A	A	A	A	A	A
◊	A	A	A	A	A	A	A	A	A	A	A	A	A	A
◐	A	A	A	A	A	A	A	A	A	A	A	A	A	A

○ ◊ ◐ 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

A = 48 standard contacts L=4,5

Marking	Standard
Performance level	G2/0 = Contact area level2 / Termination tin
Flux proof	no
Fixing clip	yes
Dimensions	SDA-85042-0002 sht.1
Technical Data	PS-85042-0001

A	G2/0	a1-l6	b1-l6	c1-l6
Contact symbol	Perform. level	Contact position number		

REVISIONS				
ECN MC1998-2748	first release			

FOR PREVIOUS REVISIONS SEE MRI LIST	DRWG BY	SIGN	CADCAM PROJECT NAME	SH. REV.
	KN		s8504242	
	CHK'D BY	SIGN	s31	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. & SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION
	Cc		TITLE	
	APPD BY	SIGN	48 pos. female connector DIN 41612, style C/2 contacts arrangement	
	JB		SHEET NO. DATE	
DESIGN DIMENSION <input type="checkbox"/> MM <input type="checkbox"/> IN.	SCALE	1 OF 1 98/03/09		
EQUIVALENT DIMENSION <input type="checkbox"/> MM <input type="checkbox"/> IN.	PART NO. DWG NO. SIZE			
IF TWO DIMENSIONS ARE SHOWN, THE UPPER IS THE DESIGN DIMENSION, LOWER IS SECONDARY	85042-4232		SD-85042-4232 A	