

View on mating side

○	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
△	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
□	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A

W U V M N L O P Q R S T U V W X Y Z

- A = 16 contacts L=2,8
- B = 16 contacts L=2,8
- C = 16 contacts L=2,8

S = 48 total number of contacts

Marking	Standard
Performance level	GI/0 = Contact area level / Termination fin
Flux proof	no
Fixing clip	yes
Dimensions	SDA-85052-0002 sht.1
Technical Data	PS-85052-0001

C	GI/0	c1-l6
B	GI/0	b1-l6
A	GI/0	a1-l6
Contact symbol	Perform. level	Contact position number

ECN No. MC1999-0010 first release	REVISIONS		FOR PREVIOUS REVISIONS SEE MRI LIST	
	LTR			
UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ± 2° INCH METRIC		DRWG BY Cc	SIGN	
3 PLACE ± .	±	CHK'D BY Er	SIGN	
2 PLACE ± .	±	APP'D BY FB	SIGN	
1 PLACE ± .	±	SCALE		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		DESIGN DIMENSION	<input type="checkbox"/> MM <input type="checkbox"/> IN.	
		EQUIVALENT DIMENSION	<input type="checkbox"/> MM <input type="checkbox"/> IN.	
IF TWO DIMENSIONS ARE SHOWN, THE UPPER IS THE DESIGN DIMENSION, LOWER IS SECONDARY				
REVISE ONLY ON CAD SYSTEM		CAD/CAM PROJECT NAME S8505209 s01	SH. REV.	
TITLE 48 pos. female connector acc. DIN 41612 style R/2 contacts arrangement		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. & SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		
PART NO. 85052-0907		DWG NO. SD-85052-0907		SIZE A
		SHEET NO. 1 OF 1		DATE 98/07/17

