

# › Millenium 3 PLC Smart Compact CD12/CB12 With/without display

- › Highly visible blue LCD display with 4 lines of 18 characters, with controllable backlighting
- › Compatible with the whole of the specific function blocks library of the software workshop
- › Extended temperature range (-20 °C → +70 °C)
- › Analogue inputs 0-10 V<sub>DC</sub>, potentiometer, NTC, (0-20mA/Pt100 with adapters)
- › Selectable parameter setting: option to choose the parameters settable from the front panel



CD12 with display



CB12 without display

Selection guide				
Power supply	Inputs	Outputs	CD12	CB12
12 V <sub>DC</sub>	8 digital of which 4 analogue	4 relays 8A	<b>88974045</b>	-
12 V <sub>DC</sub>	8 digital of which 4 analogue	4 solid state 0.5A of which 1 is PWM	<b>88974046</b>	<b>88974026</b>
24 V <sub>DC</sub>	8 digital of which 4 analogue	4 relays 8A	<b>88974041</b>	<b>88974021</b>
24 V <sub>DC</sub>	8 digital of which 4 analogue	4 solid state 0.5A of which 1 is PWM	<b>88974042</b>	-
24 V <sub>AC</sub>	8 digital	4 relays 8A	<b>88974044</b>	<b>88974024</b>
100 → 240 V <sub>AC</sub>	8 digital	4 relays 8A	<b>88974043</b>	<b>88974023</b>

Accessories		
Type	Description	Code
M3 Soft	Multilingual programming software with the specific functions library	<b>88970111</b>
PA	EEPROM memory cartridge	<b>88970108</b>
PA	3m serial cable: PC → Millenium 3	<b>88970102</b>
PA	3m USB cable: PC → Millenium 3	<b>88970109</b>
PA	Millenium 3 → Bluetooth® interface (class A 10m)	<b>88970104</b>

12 V <sub>DC</sub>	24 V <sub>DC</sub>	24 V <sub>AC</sub>	100 → 240 V <sub>AC</sub>
--------------------	--------------------	--------------------	---------------------------

General characteristics	
Product certifications (according to IEC/EN 60529)	UL, CSA, GL (*) (*) GL: except for 88 970 xxx
Conforms to the Low Voltage directive (according to 73/23/EEC)	EN (IEC) 61131-2 (Open equipment)
Conforms to the EMC directive (according to 89/336/EEC)	EN (IEC) 61131-2 (Zone B) EN (IEC) 61000-6-2, EN (IEC) 61000-6-3 (*), EN (IEC) 61000-6-4 (* Except for configurations (88 970 1x1 or 88 970 1x2) + (88 970 250 or 88 970 270) + 88 970 241 class A (class B: work in progress)
Grounding	None
Degree of protection (according to IEC/EN 60529)	IP 40 for front panel IP 20 for terminal block
Over-voltage category (according to IEC/EN 60664-1)	3

	12 V <sub>DC</sub>	24 V <sub>DC</sub>	24 V <sub>AC</sub>	100 → 240 V <sub>AC</sub>
Degree of interference (according to IEC/EN 61131-2)	2			
Maximum allowable altitude	For operation: 2000m For transport: 3048m			
Mechanical strength	Vibration resistance IEC/EN 60068-2-6, test Fc Shock resistance IEC/EN 60068-2-27, test Ea			
Electrostatic discharge withstand	Electrostatic discharge immunity IEC/EN 61000-4-2, level3			
HF interference withstand (immunity)	Radiated electromagnetic field immunity IEC/EN 61000-4-3, level 3 Fast transient/burst immunity IEC/EN 61000-4-4, level 3 Surge immunity IEC/EN 61000-4-5 Common mode radio frequency IEC/EN 61000-4-6, level 3 Voltage dips and interruptions (~) IEC/EN 61000-4-11 Damped oscillatory wave immunity IEC/EN 61000-4-18			
Conducted and radiated interference (according to EN 55022/11 group 1)	Class B(*) (*) Except for configurations (88 970 1x1 or 88 970 1x2) + (88 970 250 or 88 970 270) + 88 970 241 class A (class B: work in progress)			
Operating temperature	-20 → +70 °C (+40 °C in unventilated cabinet) according to IEC/EN 60068-2-1 and IEC 60068-2-2 Duty cycle 100% (6A relay) Duty cycle 66% (8A relay)			
Storage temperature	-40 → +80 °C			
Relative humidity	95 % max. (non-condensing)			
Connection capacity to screw terminal (Tightened by screwdriver of 3.5mm diameter)	Flexible wire with single conductor terminal end:	0.25 to 2.5 mm <sup>2</sup> 2 conductors 0.25 to 0.75 mm <sup>2</sup>		
	Semi-rigid single conductor wire:	0.2 to 2.5 mm <sup>2</sup>		
	Rigid single conductor wire:	0.2 to 2.5 mm <sup>2</sup> 2 conductors 0.2 to 1.5 mm <sup>2</sup>		
	Tightening torque	0.5 Nm		

**Processing characteristics**

LCD display	CD: display with 4 lines of 18 characters			
Programming method	Ladder or function blocks / SFC (Grafcet)			
Ladder program size	Ladder: 120 lines Function blocks: 350 typical blocks			
Program memory	Flash EEPROM			
Removable memory	EEPROM			
Data memory	368 bits / 200 words			
Backup time (in the event of a power failure)	Program and settings in PLC 10 years Program and settings on removable memory 10 years Data memory 10 years			
Cycle time	Ladder: 20 ms typically Function blocks: 6 to 90 ms			
Response time	Input data acquisition time + 1 to 2 cycles			
Clock running time	10 years (lithium battery) at 25 °C			
Clock drift	Drift < 12 min/year (at 25 °C) 6 s/month (at 25 °C and calibrated)			
Accuracy of delay blocks	1% +- 2 cycles			

**Power supply**

	12 V <sub>DC</sub>	24 V <sub>DC</sub>	24 V <sub>AC</sub>	100 - 240 V <sub>AC</sub>
Nominal voltage	12 V <sub>DC</sub>	24 V <sub>DC</sub>	24 V <sub>AC</sub>	100 - 240 V <sub>AC</sub>
Operating limits	(-13 % / +20 %) 10.4 → 14.4 V <sub>DC</sub>	(-20 % / +25 %) 19.2 → 30 V <sub>DC</sub>	(-15 % / +20 %) 20.4 V <sub>AC</sub> → 28.8 V <sub>AC</sub>	(-15 % / +10 %) 85 - 264 V <sub>AC</sub>
Operating frequency	N/A		50/60 Hz (+4 %/-6 %) 47 to 53 Hz / 57 to 63 Hz	
Startup time from power on	< 1.2s			
Micro-break immunity	≤ 1 ms (repeated 20 times)		10 ms (repeated 20 times)	

	12 V <sub>DC</sub>	24 V <sub>DC</sub>	24 V <sub>AC</sub>	100 → 240 V <sub>AC</sub>
Maximum power draw	CD12 - CB12: 1.5 W CD12 - CB12 with solid state output: 1.5 W	CD12 - CB12: 4 W CD12 - CB12 with solid state output - 3 W	CD12 - CB12: 4 VA	CD12 - CB12: 7 VA
Inverted polarity protection	Yes		N/A	
Effective insulation voltage	N/A		1780 V (50-60 Hz)	

**Digital inputs**

Position of the inputs	4 inputs from I1 to I4		8 inputs from I1 to IE	
Input voltage	12 V <sub>DC</sub> (-13 % / +20 %)	24 V <sub>DC</sub> (-20 % / +25 %)	24 V <sub>AC</sub> (-15% / +20 %)	100 → 240 V <sub>AC</sub> (-15 % / +10 %)
Input current	3.9 mA @ 10.44 V <sub>DC</sub> 4.4 mA @ 12.0 V <sub>DC</sub> 5.3 mA @ 14.4 V <sub>DC</sub>	2.6 mA @ 19.2 V <sub>DC</sub> 3.2 mA @ 24.0 V <sub>DC</sub> 4.0 mA @ 30.0 V <sub>DC</sub>	4.4 mA @ 20.4 V <sub>AC</sub> 5.2 mA @ 24.0 V <sub>AC</sub> 6.3 mA @ 28.8 V <sub>AC</sub>	0.24 mA @ 85 V <sub>AC</sub> 0.75 mA @ 264 V <sub>AC</sub>
Input impedance	6.45 kΩ	7.4 kΩ	4.6 kΩ	350 kΩ
Logic state 1 triggering voltage	≥ 7 V <sub>DC</sub>	≥ 15 V <sub>DC</sub>	≥ 14 V <sub>AC</sub>	≥ 79 V <sub>AC</sub>
Logic state 1 triggering current	≥ 2 mA	≥ 2.2 mA	> 2 mA	> 0.17 mA
Logic state 0 triggering voltage	≤ 3 V <sub>DC</sub>	≤ 5 V <sub>DC</sub>	≤ 5 V <sub>AC</sub>	≤ 40 V <sub>AC</sub>
Logic state 0 triggering current	< 0.9 mA	< 0.75 mA	< 0.5 mA	
Response time	1 → 2 cycles + 6 ms		50 ms	
Sensor type	Contact or 3 wire PNP			
Galvanic isolation	No			
Status indication	On the LCD screen for CD and XD			

**Analogue or digital inputs**

**Inputs used in analogue mode**

Position of the inputs	4 inputs from IB to IE		-
Measurement range	(0 → 10 V) or (0 → V <sub>supply</sub> )	0 → 10 V or 0 → V <sub>supply</sub>	N/A
Input impedance	14 kΩ	12 kΩ	N/A
Maximum input voltage	14.4 V <sub>DC</sub>	30 V <sub>DC</sub>	N/A
LSB value	14 mV	29 mV	N/A
Input type	Common mode		N/A
Resolution	10 bits		N/A
Conversion time	PLC cycle time		N/A
Precision at 25 °C	± 5 %		N/A
Precision at 55 °C	± 6.2 %		N/A
Repeatability at 55 °C	± 2 %		N/A
Analogue channel to power supply isolation	None		N/A
Cabling distance	10 m maximum, with shielded cable (sensor not isolated)		N/A
Inverted polarity protection	Yes		N/A
Potentiometer control	2.2 kΩ / 0.5 W (Preset) 10 kΩ max.		N/A

**Inputs in digital mode**

Position of the inputs	4 inputs from IB to IE		-
Input voltage	12 V <sub>DC</sub> (-13 % / +20 %)	24 V <sub>DC</sub> (-20 % / +25 %)	N/A
Input current	0.7 mA @ 10.44 V <sub>DC</sub> 0.9 mA @ 12.0 V <sub>DC</sub> 1.0 mA @ 14.4 V <sub>DC</sub>	1.6 mA @ 19.2 V <sub>DC</sub> 2.0 mA @ 24.0 V <sub>DC</sub> 2.5 mA @ 30.0 V <sub>DC</sub>	N/A
Input impedance	14 kΩ	7.4 kΩ	N/A
Logic state 1 triggering voltage	≥ 7 V <sub>DC</sub>	≥ 15 V <sub>DC</sub>	N/A
Logic state 0 triggering voltage	≤ 3 V <sub>DC</sub>	≤ 5 V <sub>DC</sub>	N/A

	12 V <sub>DC</sub>	24 V <sub>DC</sub>	24 V <sub>AC</sub>	100 → 240 V <sub>AC</sub>
Response time	1 → 2 cycles + 6 ms		N/A	
Sensor type	Contact or 3 wire PNP		N/A	
Galvanic isolation	No		N/A	
Status indication	On the LCD screen for CD and XD		N/A	

**Relay outputs**


Maximum breaking voltage	5 to 150 V <sub>DC</sub> 24 to 250 V <sub>AC</sub>
Cut-off current / thermal	CB-CD: 8 A
Electrical lifetime of 500.000 operations	Usage category DC-12: 24 V, 1.5 A Usage category DC-13: 24 V (L/R = 10 ms), 0.6 A Usage category AC-12: 230 V, 1.5 A Usage category AC-15: 230 V, 0.9 A
Minimum switching current (with minimum voltage of 12 V)	10 mA
Contact reliability at low levels	12 V, 10 mA
Maximum operating frequency	Unloaded: 10 Hz At rated current: 0.1 Hz
Mechanical lifetime	10 000 000 operating cycles
Rated impulse withstand voltage (according to IEC/EN 60947-1 and et IEC/EN 60664-1)	4 kV
Response time	Make 10 ms Break 5 ms
Built-in protections	Against short-circuits: None Against over-voltages and over-currents: None
Status indication	On the LCD screen for CD and XD

**Solid state digital/PWM outputs (Only on VDC model)**


Solid state PWM outputs	O4	-
Cut-off voltage / operating limit	19.2-30 V <sub>DC</sub>	-
Nominal voltage	24 V <sub>DC</sub>	-
Nominal current	0.5 A	-
Maximum breaking current	0.625 A	-
State 1 output voltage drop	≤ 2 V at I = 0.5 A	-
Response time	Make ≤ 1 ms Break ≤ 1 ms	-
Frequency	1 Hz maximum for inductive load	-
Built-in protections	Against over-voltages and short-circuits: Yes Against over-voltages (*): Yes Against power supply reversal: Yes	-
Minimum load	0.1 A	-
Maximum incandescent load	0.1 mA / 24 V <sub>DC</sub>	-
Galvanic isolation	No	-
PWM frequency	14.11 Hz 56.45 Hz 112.90 Hz 225.80 Hz 451.59 Hz 1.806.37 Hz	-
PWM duty cycle	0 → 100 % (256 steps for CD,XD and 1024 steps for XA)	-

	12 V <sub>DC</sub>	24 V <sub>DC</sub>	24 V <sub>AC</sub>	100 → 240 V <sub>AC</sub>
PWM accuracy at 120 Hz	< 5% (from 20 % → 80 %) load at 10 mA		-	-
PWM accuracy at 500 Hz	< 10% (from 20 % → 80 %) load at 10 mA		-	-
PWM maximum breaking current	50mA	50 mA	-	-
Maximum cable length for PWM	20 m		-	-
Status indication	On the LCD screen for CD and XD		-	-

**Schematics**  
**Footprint**  
**Version**



**Input/output wiring**  
**Inputs 12 V<sub>DC</sub>, 24 V<sub>DC</sub>**



**Inputs 100-240 V<sub>AC</sub>, 24 V<sub>AC</sub>**

