

Product availability: Non-Stock - Not normally stocked in distribution facility

### Main

Device short name	A
Enclosure type	Standard environment enclosure indoor
Product specific application	Mechanically alternating the operation of two pumps or motors
Switch application	Standard

### Complementary

Electrical connection	Screw clamp terminal
Material	Stainless steel float/rod Nitrile (Buna-N) seal ring
Motor power hp	1 hp at 460/575 V AC for 3 phases 2 hp at 115 V AC for 1 phase 3 hp at 115 V AC for 3 phases 3 hp at 230 V AC for 1 phase 5 hp at 230 V AC for 3 phases
Mounting support	Flange
Number of poles	2
Permissible voltage	<= 575 V AC
Switch function	DPST

### Environment

NEMA degree of protection	NEMA 1
---------------------------	--------

### Ordering and shipping details

Category	21601 - 9037,9038 COMMERCIAL FLOAT SWITCHES
Discount Schedule	CP7G
GTIN	00785901591047
Nbr. of units in pkg.	1
Package weight(Lbs)	4.490000000000002
Returnability	N
Country of origin	MX

### Offer Sustainability

RoHS (date code: YYWW)	Will not be compliant
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available
California proposition 65	WARNING: This product can expose you to chemicals including:
----- Substance 1	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
----- Substance 2	Diisodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
----- More information	For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>

## Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---