

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Device short name	A
Enclosure type	Hazardous location enclosure indoor
Product specific application	Mechanically alternating the operation of two pumps or motors
Switch application	Standard

Complementary

Electrical connection	Screw clamp terminal
Material	Stainless steel float/rod Nitrile (Buna-N) seal ring
Motor power hp	1 hp at 460/575 V AC for 3 phases 2 hp at 115 V AC for 1 phase 3 hp at 115 V AC for 3 phases 3 hp at 230 V AC for 1 phase 5 hp at 230 V AC for 3 phases
Mounting support	Flange
Number of poles	2
Permissible voltage	<= 575 V AC
Switch function	DPST

Environment

NEMA degree of protection	NEMA 7/9
---------------------------	----------

Ordering and shipping details

Category	21601 - 9037,9038 COMMERCIAL FLOAT SWITCHES
Discount Schedule	CP7G
GTIN	00785901457169
Nbr. of units in pkg.	1
Package weight(Lbs)	8.7300000000000004
Returnability	N
Country of origin	MX

Offer Sustainability

RoHS (date code: YYWW)	Will not be compliant
REACH	Reference not containing SVHC above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including:
----- Substance 1	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
----- Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
----- More information	For more information go to www.p65warnings.ca.gov