


900 Series SMA

50 Ohm Cable and PCB Connectors



Bomar products, like the 900 Series 50 Ohm SMA Connectors, are now sold under the Win™ brand from Winchester Interconnect™.

Product Description

Winchester Interconnect's 900 Series 50 Ohm SMA Connectors can be used in a wide range of applications including Test and Measurement, Mil-Aero, Satellite, and Wireless Communication Equipment.

Our 900 Series 50 Ohm SMA Connectors are designed in accordance with MIL-STD 348 and feature a .250-36 threaded coupling interface designed for a frequency range of DC to 18 GHz.

Male cable plug connectors are available in straight and right-angle designs for popular flexible and semi-rigid cables.

Printed Circuit Board (PCB) connectors are available in straight and right-angle through-hole solder, and also in our unique E-Snap® Edge-Mount design.



- Threaded coupling ensures connector will not decouple in vibration-intensive applications.



- Straight crimp plug center contact features a retention barb which snaps into the insulator to prevent the pin contact from backing out of the connector.



- E-Snap® Edge-Mount connectors provide superior RF performance versus traditional right-angle connectors, as a straight contact provides the best transmission path.

 **Winchester**
Interconnect.

We Energize Innovation.

Specifications

Electrical	Dielectric	Mechanical	Material	Environmental
Impedance 50 Ohms	Withstanding Voltage <i>Flexible</i> 1000 VRMS <i>Semi-Rigid</i> 1500 VRMS	Coupling Mating Torque 7 – 15 in-lbs.	Body Material Brass	Temperature Range -65°C to +165°C
Polarity <i>Standard</i>	Contact Resistance Center ≤ 2 Megohms Outer ≤ 2 Megohms	Cable Retention <i>Flexible</i> 60 lbs. Min <i>Semi-Rigid</i> 80 lbs. Min	Body Finish Nickel or Gold	
Frequency Range <i>Flexible Cable</i> 0 to 12.5 GHz <i>Semi-Rigid</i> 0 to 18 GHz	Insulation Resistance 5000 Megohms Min	Center Contact Solder/Crimp	Contact Material Male Brass Female BECU	
VSWR <i>Straight</i> 1.15 Max <i>R/A</i> 1.2 Max		Connector Durability 500 Cycles Min	Insulator Material PTFE	
			Contact Finish Gold	

Part Numbers

Part Number	Straight and Right-Angle Cable Plugs	Crimp Tool	Hex Size
910A204M	Straight Plug for RG174, RG316, LMR100	BDHD200	Solder / 0.128
910A204F	Straight Plug for RG58, RG58A, RG141, LMR195	BDHD200	Solder / 0.213
910A204P	Straight Plug for RG55, RG142, RG223, RG400	BDHD200	Solder / 0.213
910A704HV	Straight Plug RG402 (use cable for center contact)	Solder	Solder
910A704B	Straight Plug RG402 Cable (with center contact supplied)	Solder	Solder
910A704A	Straight Plug RG405 Cable (with center contact supplied)	Solder	Solder
913A204M	Right-Angle Plug for RG174, RG316, LMR100	BDHD200	Solder / 0.128
913A204F	Right-Angle Plug for RG58, RG142, RG223, LMR195	BDHD200	Solder / 0.213
913A204P	Right-Angle Plug for RG55, RG142, RG223, RG400	BDHD200	Solder / 0.213
913A704B	Right-Angle Plug for RG402	Solder	Solder
913A704A	Right-Angle Plug for RG405	Solder	Solder

Part Number	Printed Circuit Board Connectors	PCB Thickness	Packaging
961A514	Vertical, SMA, Jack, 0.155" Solder Tail	0.062"	Single
964A595	Right-Angle, SMA, Jack, 0.155" Solder Tail	0.062"	Single
960A514	Vertical, SMA, Plug, 0.155" Solder Tail	0.062"	Single
963A595	Right-Angle, SMA, Plug, 0.155" Solder Tail	0.062"	Single
961E504	E-Snap® Edge-Mount, SMA, Jack	0.062"	Single
962E504	E-Snap® Edge-Mount, SMA, Plug	0.062"	Single
961E504HF	High Frequency E-Snap® Jack (26.5 GHz)	0.062"	Single



Bomar products are now under the Win™ brand from Winchester Interconnect.