

**Product: 9204** ☑



MIL-C-17G, RG59, 75 Ohm Coax, #23 Solid BCCS, 95% BC Braid, CMH

# **Product Description**

23 awg solid .023" bare copper-covered steel conductor, polyethylene insulation, bare copper braid shield (95% coverage), non-contaminating PVC jacket.

### **Technical Specifications**

### **Physical Characteristics (Overall)**

# Conductor AWG Stranding Material Nominal Diameter No. of Coax 23 Solid BCCS - Bare Copper Covered Steel 0.023 in 1 Conductor Count: 1 Insulation Material Nominal Diameter PE - Polyethylene 0.145 in Outer Shield Type Material Coverage [%] Braid Bare Copper (BC) 95% Outer Jacket Material Nominal Diameter PVC - Polyvinyl Chloride (Non-Contaminating) 0.242 in

### **Electrical Characteristics**

### **Conductor DCR**

Nominal Conductor DCR	Nominal Conductor DCR Conductor Resistance	Nominal Outer Shield DCR	Outer Conductor DCR
47 Ohm/1000ft	47 Ohm/1000ft	2.6 Ohm/1000ft	2.6 Ohm/1000ft

# Capacitance

Nom. Capacitance Conductor to Shield 20.5 pF/ft

### Inductance

Nominal Inductance

### Impedance

Nominal Characteristic Impedance
75 Ohm

### High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.6 dB/100ft
10 MHz	1.1 dB/100ft

50 MHz	2.4 dB/100ft
100 MHz	3.4 dB/100ft
200 MHz	4.9 dB/100ft
400 MHz	7 dB/100ft
700 MHz	9.7 dB/100ft
900 MHz	11.1 dB/100ft
1000 MHz	12 dB/100ft

### Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.54 ns/ft	66%

# High Frequency

Frequency [MHz]	Max. Insertion Loss (Attenuation)
400 MHz	9 dB/100ft
1000 MHz	16 dB/100ft

# Power Rating

Frequency [MHz]	Max. Power Rating [W]
50 MHz	450 W
100 MHz	300 W
200 MHz	200 W
400 MHz	130 W
700 MHz	95 W
900 MHz	80 W
1,000 MHz	72 W

### Voltage

Non-UL Voltage Rating 1700 V RMS

# **Temperature Range**

Non-UL Temp Rating:	85°C
Operating Temp Range:	-40°C To +85°C

# **Mechanical Characteristics**

Bulk Cable Weight:	36 lbs/1000ft
Max. Pull Tension:	78 lbs
Min. Bend Radius/Minor Axis:	2.5 in

# Standards

NEC/(UL) Compliance:	СМН
CEC/C(UL) Compliance:	СМН
RG Type:	59
Military Compliance:	MIL-DTL-17, M17/29-RG59, QPL

# **Applicable Environmental and Other Programs**

Environmental Space:	Indoor (Not Riser or Plenum)
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	No
MII Order #39 (China RoHS):	Yes

# Suitability

Suitability - Indoor:	Yes

# Flammability, LS0H, Toxicity Testing