

Product: [9907](#) 



Thinnet 10BASE2, #20, FPO, Duobond II+TC Braid, PVC Jkt, CM

Product Description

IEEE 802.3 Ethernet Thinnet 10BASE2, 20 AWG stranded (19x32) .037" tinned copper conductor, foam polyethylene insulation, Duobond® II (100% coverage) + an overall tinned copper braid shield (93% coverage), PVC jacket.

Technical Specifications

Product Overview

Suitable Applications:	Thin Ethernet
------------------------	---------------

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Coax
20	19x32	TC - Tinned Copper	0.037 in	1

Conductor Count:	1
------------------	---

Insulation

Material	Nominal Diameter
PE - Polyethylene (Foam)	0.102 in

Outer Shield

Type	Layer	Material	Material Trade Name	Coverage [%]
Tape	1	Tri-Laminate (Alum+Poly+Alum)	Duofoil®	100%
Braid	2	Tinned Copper (TC)		93%

Outer Jacket

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.185 in
	0.279 in

Electrical Characteristics

Conductor DCR

Max. Conductor Loop	Nominal Conductor DCR	Nominal Outer Shield DCR	Outer Conductor DCR
15.24 Ohm/1000ft	8.8 Ohm/1000ft	5.8 Ohm/1000ft	5.8 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Shield
25.4 pF/ft

Inductance

Nominal Inductance
0.27 µH/m

Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance
50 Ohm	± 2 Ohm

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.43 dB/100ft
10 MHz	1.3 dB/100ft
50 MHz	2.91 dB/100ft
100 MHz	4.2 dB/100ft
200 MHz	6.1 dB/100ft
400 MHz	8.9 dB/100ft
700 MHz	12.1 dB/100ft
900 MHz	13.9 dB/100ft
1000 MHz	14.8 dB/100ft

Delay

Max. Delay Skew	Nominal Delay	Nominal Velocity of Propagation (VP) [%]
80 ns/100m	1.27 ns/ft	80%

Voltage

UL Description	UL Voltage Rating
	300 V RMS
UL AWM Style 1354	30 V RMS

Electrical Characteristics Notes:	UL AWM 1354: 30 V RMS
-----------------------------------	-----------------------

Temperature Range

UL Temp Rating:	60°C
Operating Temp Range:	-40°C To +80°C

Mechanical Characteristics

Bulk Cable Weight:	23 lbs/1000ft
Max. Pull Tension:	45 lbs
Min. Bend Radius/Minor Axis:	2 in

Standards

Customer Reference Document:	DEC Part No. 17-01248-00
NEC/(UL) Compliance:	CL2, CM
CEC/C(UL) Compliance:	CM
UL AWM Style Compliance:	1354 (30 V 60°C)
CPR Euroclass:	Eca
IEEE Compliance:	802.3 10Base2
RG Type:	58
Other Standards:	ISO8802.3 10Base2

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes
-----------------------	-----

Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 UL Loading
IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS