



60×60×15 mm

San Ace 60 9GA type Low Power Consumption Fan

General Specifications

- Material Frame: Plastic (Flammability: UL 94V-0), Impeller: Plastic (Flammability: UL 94V-0)
- Expected life See the table below. (L10 life: 90% survival rate for continuous operation in free air at 60°C, rated voltage)
- Motor protection function Locked rotor burnout protection, Reverse polarity protection
For details, please refer to p. 547.
- Dielectric strength 50/60 Hz, 500 VAC, for 1 minute (between lead wire conductors and frame)
- Insulation resistance 10 MΩ or more with a 500 VDC megger (between lead wire conductors and frame)
- Sound pressure level (SPL) At 1 m away from the air inlet
- Storage temperature -30 to +70°C (Non-condensing)
- Lead wire ⊕Red ⊖Black (Sensor) Yellow (Control) Brown
(For models without PWM control function, there is no speed control wiring.)
- Mass 50 g

Specifications

The models listed below **have ribs and pulse sensors with PWM control function.**

| Model no. | Rated voltage [V] | Operating voltage range [V] | PWM duty cycle* [%] | Rated current [A] | Rated input [W] | Rated speed [min ⁻¹] | Max. airflow [m ³ /min] [CFM] | Max. static pressure [Pa] [inchH ₂ O] | SPL [dB (A)] | Operating temperature [°C] | Expected life [h] |
|----------------|-------------------|-----------------------------|---------------------|-------------------|-----------------|----------------------------------|--|--|--------------|----------------------------|----------------------------|
| 9GA0612P7G01 | 12 | 10.2 to 13.8 | 100 | 0.16 | 1.92 | 5900 | 0.68 24 | 80 0.32 | 38 | -20 to +70 | 40000/60°C (70000/40°C) |
| | | | 0 | 0.05 | 0.6 | 1500 | 0.17 6.0 | 5.2 0.02 | 10 | | |
| 9GA0612P7H01 | 12 | 10.2 to 13.8 | 100 | 0.1 | 1.2 | 4900 | 0.56 19.7 | 55.6 0.223 | 34 | | |
| | | | 0 | 0.03 | 0.36 | 1300 | 0.15 5.3 | 3.9 0.015 | 8 | | |
| 9GA0624P7G01** | 24 | 20.4 to 27.6 | 100 | 0.08 | 1.92 | 5900 | 0.68 24.0 | 80 0.32 | 38 | | |

* PWM frequency: 25 kHz ** Fan does not rotate when PWM duty cycle is 0%.

The following sensor and control options are available for selection.

Available for all models. **Without sensor**

Differs according to the model. Refer to the table on p. 571. **Pulse sensor** **Lock sensor**

The models listed below **have ribs and pulse sensors.**

| Model no. | Rated voltage [V] | Operating voltage range [V] | Rated current [A] | Rated input [W] | Rated speed [min ⁻¹] | Max. airflow [m ³ /min] [CFM] | Max. static pressure [Pa] [inchH ₂ O] | SPL [dB (A)] | Operating temperature [°C] | Expected life [h] |
|-------------|-------------------|-----------------------------|-------------------|-----------------|----------------------------------|--|--|--------------|----------------------------|----------------------------|
| 9GA0612G701 | 12 | 6 to 13.8 | 0.16 | 1.92 | 5900 | 0.68 24 | 80 0.32 | 38 | -20 to +70 | 40000/60°C (70000/40°C) |
| 9GA0612H701 | | | 0.1 | 1.2 | 4900 | 0.56 19.7 | 55.6 0.223 | 34 | | |
| 9GA0612M701 | | | 0.08 | 0.96 | 3900 | 0.45 15.9 | 35.3 0.142 | 28 | | |
| 9GA0612L701 | | | 0.03 | 0.36 | 2800 | 0.31 10.9 | 18 0.072 | 17 | | |
| 9GA0624M701 | 24 | 12 to 27.6 | 0.05 | 1.2 | 3900 | 0.45 15.9 | 35.3 0.142 | 28 | | 40000/60°C (70000/40°C) |

The following sensor and control options are available for selection.

Available for all models. **Without sensor**

Differs according to the model. Refer to the table on pp. 570 to 571. **Lock sensor** **PWM control**




Airflow - Static Pressure Characteristics / PWM Duty - Speed Characteristics Example

9GA0612P7G01 With pulse sensor with PWM control function

PWM duty cycle

Operating voltage range


PWM duty - Speed characteristics example




Airflow - Static Pressure Characteristics / PWM Duty - Speed Characteristics Example

9GA0612P7H01 With pulse sensor with PWM control function


PWM duty cycle



Operating voltage range




PWM duty - Speed characteristics example




9GA0624P7G01 With pulse sensor with PWM control function


PWM duty cycle



Operating voltage range




PWM duty - Speed characteristics example




9GA0612G701 With pulse sensor

Operating voltage range




9GA0612H701 With pulse sensor

Operating voltage range




9GA0612M701 With pulse sensor

Operating voltage range



9GA0612L701 With pulse sensor

Operating voltage range



9GA0624M701 With pulse sensor

Operating voltage range

