

### SMA Male Plug to SSMA Male Plug

Model Number

ADT-2695-SM-SSM-02


**SPECIFICATIONS**

**Frequency:** DC - 25.0 GHz

**VSWR:** 1.06 + .009 f (GHz) @ DC-12.4 GHz  
1.05 + .01 f (GHz) @ 12.4-25.0 GHz

**Impedance:** 50 Ohms

**Finish:** Passivated Stainless Steel



### SMA Male Plug to SSMA Female Jack

Model Number

ADT-2696-SM-SSF-02


**SPECIFICATIONS**

**Frequency:** DC - 25.0 GHz

**VSWR:** 1.06 + .009 f (GHz) @ DC-12.4 GHz  
1.05 + .01 f (GHz) @ 12.4-25.0 GHz

**Impedance:** 50 Ohms

**Finish:** Passivated Stainless Steel



### SMA Female Jack to SSMA Male Plug

Model Number

ADT-2697-SF-SSM-02


**SPECIFICATIONS**

**Frequency:** DC - 25.0 GHz

**VSWR:** 1.06 + .009 f (GHz) @ DC-12.4 GHz  
1.05 + .01 f (GHz) @ 12.4-25.0 GHz

**Impedance:** 50 Ohms

**Finish:** Passivated Stainless Steel



### SMA Female Jack to SSMA Female Jack

Model Number

ADT-2698-SF-SSF-02

**SPECIFICATIONS**

**Frequency:** DC - 25.0 GHz

**VSWR:** 1.06 + .009 f (GHz) @ DC-12.4 GHz  
1.05 + .01 f (GHz) @ 12.4-25.0 GHz

**Impedance:** 50 Ohms

**Finish:** Passivated Stainless Steel

