In-Series Adapters

SMA Types

Right Angle SMA Male Plug to SMA Female Jack

Model Number

ADT-8000-MF-SMA-02

SPECIFICATIONS

Frequency: DC - 18.0 GHz VSWR: 1.05 + .010 f (GHz) Impedance: 50 Ohms

Finish: Passivated Stainless Steel

.50 .583



Formerly SMA-028-8000 and SMA-8000-28-000-02

Right Angle SMA Female Jack to SMA Female Jack

Model Number

ADT-8000-FF-SMA-02

SPECIFICATIONS

Frequency: DC - 18.0 GHz VSWR: 1.05 + .010 f (GHz) Impedance: 50 Ohms

Finish: Passivated Stainless Steel

.583



Formerly SMA-026-8000 and SMA-8000-26-000-02

Right Angle SMA Male Plug to SMA Male Plug


Model Number

ADT-8000-MM-SMA-02

SPECIFICATIONS

Frequency: DC - 18.0 GHz VSWR: 1.05 + .010 f (GHz) Impedance: 50 Ohms

Finish: Passivated Stainless Steel





SMA Female Jack to SMA Female Jack - Blkhd Mount - Hermetic


Model Number

ADT-2824-FF-SMA-02

SPECIFICATIONS

Frequency: DC - 18.0 GHz VSWR: 1.10 + .010 f (GHz) Impedance: 50 Ohms

Finish: Passivated Stainless Steel





Standard finish is passivated stainless steel, for gold plating change -02 suffix to -00.

