



REVISIONS				
REV.	DESCRIPTION	REASON	DATE	DESIGNED
0	PROPOSED	PRODUCTION	20DEC05	H.K
1	REVISED	CORRECTED PART NUMBER	23FEB06	H.K
2	REVISED	ADDED NEW PLATING	02FEB07	H.K
3	REVISED	CHANGED PLATING	08FEB07	H.K
4	REVISED AND REDRAWING	GM P/N ADDED	22FEB08	T.H



- NOTES:
- 1) TOLERANCES ARE, IF NOT SPECIFIED, ± 0.3
 - 2) APPLICABLE CABLES: INSULATION O.D. ≤ 1.9
 SAE/AVSS/CAVS CABLE: AWG 22-20 <P/N: SAITW-A03T-064>
 SAE/AVSS/CAVS CABLE: AWG 18 <P/N: SAITW-A02T-064>
 - 3) TO MEET GMW3191 STANDARD.
 - 4) TEMPERATURE RANGE: CLASS 3, -40°C TO 125°C
 - 5) APPLICABLE CRIMP SPECIFICATION: # DSP-05965-HK

④	2	MALE	SAITW-A03T-064	BRASS	PRE-TIN	SIZE: S
	1	TERMINAL	SAITW-A02T-064			SIZE: M
NO.	PART NAME	PART NUMBER	MATERIAL	FINISH	REMARKS	
SIZE	UNIT	SCALE	PROJECTION	DATE	CUSTOMER	
B	METRIC	4:1		08FEB07		
APPROVED	CHECKED	DESIGNED	DRAWN	SERIES NAME	064 AIT-W MALE TERMINAL	
P. C	A. F	T. H	K. F	PART No.	SAITW-A< >T-064 ④	
JST CORPORATION				DRAWING No.	KRD-AD080	R4



SAITW-A02T-064	19167034
SAITW-A03T-064	19167033
JST PART NUMBER	TOOLED GM P/N

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO J.S.T. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.