



| REVISIONS | | | | |
|-----------|-----------------------|-----------------------|---------|----------|
| REV. | DESCRIPTION | REASON | DATE | DESIGNED |
| 0 | PROPOSED | PRODUCTION | 20DEC05 | H.K |
| 1 | REVISED | CORRECTED PART NUMBER | 23FEB06 | H.K |
| 2 | REVISED | ADDED NEW PLATING | 02FEB07 | H.K |
| 3 | REVISED | CHANGED PLATING | 08FEB07 | H.K |
| 4 | REVISED AND REDRAWING | GM P/N ADDED | 22FEB08 | T.H |



- NOTES:
- 1) TOLERANCES ARE, IF NOT SPECIFIED, ± 0.3
 - 2) APPLICABLE CABLES: INSULATION O.D. ≤ 1.9
 SAE/AVSS/CAVS CABLE: AWG 22-20 <P/N: SAITW-A03T-064>
 SAE/AVSS/CAVS CABLE: AWG 18 <P/N: SAITW-A02T-064>
 - 3) TO MEET GMW3191 STANDARD.
 - 4) TEMPERATURE RANGE: CLASS 3, -40°C TO 125°C
 - 5) APPLICABLE CRIMP SPECIFICATION: # DSP-05965-HK

| | | | | | | |
|------------------------|-----------|-------------|----------------|-------------|-------------------------|---------|
| ④ | 2 | MALE | SAITW-A03T-064 | BRASS | PRE-TIN | SIZE: S |
| | 1 | TERMINAL | SAITW-A02T-064 | | | SIZE: M |
| NO. | PART NAME | PART NUMBER | MATERIAL | FINISH | REMARKS | |
| SIZE | UNIT | SCALE | PROJECTION | DATE | CUSTOMER | |
| B | METRIC | 4:1 | | 08FEB07 | | |
| APPROVED | CHECKED | DESIGNED | DRAWN | SERIES NAME | 064 AIT-W MALE TERMINAL | |
| P. C | A. F | T. H | K. F | PART No. | SAITW-A03T-064 ④ | |
| JST CORPORATION | | | | DRAWING No. | KRD-AD080 | R4 |



| | |
|-----------------|---------------|
| SAITW-A02T-064 | 19167034 |
| SAITW-A03T-064 | 19167033 |
| JST PART NUMBER | TOOLED GM P/N |

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO J.S.T. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.