

1. SPECIFICATION

AK-200810-MM-1C1


ITEM		SPECIFICATIONS	
01	Type	Dynamic speaker	
02	Dimension	External diameter 20 mm	
03	Rated Input Power	1.0 W	
04	Max. Input Power	1.5 W for 1 minute	
05	Impedance	$8\Omega \pm 15\%$ at 2KHz 1V	
06	Resonance Frequency (Fo)	1150 Hz $\pm 20\%$ at Fo, 1V	
07	Sound pressure level	94 dB(1.0W/0.1M) ± 3 dB	at AVE 1.0K 1.2K 1.5K 1.8KHz.
08	Frequency Range	Fo – 20 K Hz	
09	Total Harmonics Distortion	Max 10 % at 1 KHz, 1.0W	

REV NO.

REVISION NOTE

APPROVAL

DATE



WIRE: UL1571,AWG30#

CONNECTOR: Equivalent to JST SHR-02V-S-B

RoHS

TITLE: DYNAMIC SPEAKER		DRAWN: Zack	2018/4/18	SCALE: 2:1	SHEET: 1:1
PART NO. AK-200810-MM-1C1		DESIGNED: R&D OF AAT		UNITS: mm	
DWC NO. CXS20037LP75-R08W1.0-B		CHECKED:		TOLERANCE ± 0.5	
		APPROVAL:		UNLESS OTHERWISE SPECIFIED:	
		MATERIAL: SPCC		ONE PLACE DECIMAL ± ***	
	REV			TWO PLACE DECIMAL ± ***	
				THREE PLACE DECIMAL ± ***	



ADVANCED ACOUSTIC TECHNOLOGY CORPORATION