


1. SPECIFICATION

AK-777708ZC-1

ITEM		SPECIFICATIONS	
01	Type	Dynamic speaker	
02	Dimension	External diameter 77 x 77 mm	
03	Rated Input Power	2.0 W	
04	Max. Input Power	3.0 W for 1 minute	
05	Impedance	$8\Omega \pm 15\%$ at 0.8KHz 1V	
06	Resonance Frequency (Fo)	300 Hz \pm 20% at Fo, 1V	
07	Sound pressure level	92 dB(1.0W/0.5M) \pm 3 dB	at AVE 1, 1.4, 1.7, 2 KHz..
		105 dB(1.0W/0.1M) \pm 3 dB	
		109 dB(2.0W/0.1M) \pm 3 dB	
08	Frequency Range	Fo – 3.0K Hz	
09	Total Harmonics Distortion	Max 10 % at 1 KHz,4V.	

REV NO.	REVISION NOTE	APPROVAL	DATE
---------	---------------	----------	------



RoHS

TITLE: DYNAMIC SPEAKER		DRAWN: Zack	2017/01/17	SCALE: 2:1	SHEET: 1:1
PART NO. AK-777708ZC-1C		DESIGNED: R&D OF AAT		UNITS: mm	
DWG NO. TQ-077F-R(94100402-1)		CHECKED:		TOLERANCE ± 0.5	
		APPROVAL:		UNLESS OTHERWISE SPECIFIED:	
REV 3		MATERIAL: SPCC		ONE PLACE DECIMAL \pm ***	
				TWO PLACE DECIMAL \pm ***	
				THREE PLACE DECIMAL \pm ***	



ADVANCED ACOUSTIC TECHNOLOGY CORPORATION