


1. SPECIFICATION

AKB-803108C-1C

ITEM		SPECIFICATIONS	
01	Type	Dynamic Speaker	
02	Dimension	External diameter 80 x 31mm	
03	Rated Input Power	2.5 W	
04	Max. Input Power	3.0 W for 1 minute	
05	Impedance	$8\Omega \pm 15\%$ at 1KHz 1V	
06	Resonance Frequency (Fo)	630 Hz $\pm 20\%$ at Fo, 1V	
07	Sound pressure level	94 dB(1.0W/0.1M) ± 3 dB	at AVE 0.8, 1.0, 1.2, 1.5 KHz.
		99 dB(2.5W/0.1M) ± 3 dB	
08	Frequency Range	Fo – 20 K Hz	
09	Total Harmonics Distortion	Max 10 % at 1 KHz, 1.5V.	

REV NO.	REVISION NOTE	APPROVAL	DATE
---------	---------------	----------	------



CONNECTOR: Equivalent to JWTA-2P(PA-2P帶扣)
 WIRE: UL 1061.AWG 26#

LABEL:
 Background: Silver
 Letters: Black

RoHS

TITLE: DYNAMIC SPEAKER		DRAWN: Zack		2016/01/26		SCALE: 1:1		SHEET: 1 : 1	
PART NO. AKB-803108C-1C		2	DESIGNED: R & D OF AAT		UNITS: mm		TOLERANCE ± 0.5		
DWG NO. YGDA8031YX-03WC450			CHECKED:		UNLESS OTHERWISE SPECIFIED:		ONE PLACE DECIMAL ± ***		
REV			APPROVAL:		TWO PLACE DECIMAL ± ***		THREE PLACE DECIMAL ± ***		
		MATERIAL: ABS							



ADVANCED ACOUSTIC TECHNOLOGY CORPORATION