


1. SPECIFICATION

AKR-28280820-MMPU-1W

ITEM		SPECIFICATIONS	
01	Type	Dynamic Speaker	
02	Rated Input Power	2.0 W	
03	Max. Input Power	3.0W for 1 minute	
04	Impedance	$8\Omega \pm 15\%$ at 1KHz 1V	
05	Resonance Frequency (Fo)	430Hz $\pm 20\%$ at Fo, 1V	
06	Sound pressure level	94dB(2.0W/0.1M) ± 3 dB	at AVE0.8, 1.0, 1.2, 1.5 KHz.
07	Frequency Range	Fo –15K Hz	
08	Total Harmonics Distortion	Max 10 % at 1 KHz, 1.0W.	
09	Magnet	Rare earth permanent (NeFeB) magnet $\Phi 12.5*2.5$ mm	

REV NO.	REVISION NOTE	APPROVAL	DATE
---------	---------------	----------	------



RoHS

TITLE: DYNAMIC SPEAKER		DRAWN: Zack	2018/08/01	SCALE: 2:1	SHEET: 1:1
PART NO. AKR-28280820-MMPU-1W		DESIGNED: R&D OF AAT	UNITS: mm		
DWG NO. CXS2828112L85-R08W2.0-B		CHECKED:	TOLERANCE ± 0.5		
REV 2		APPROVAL:	UNLESS OTHERWISE SPECIFIED:		
REV		MATERIAL: SPCC	ONE PLACE DECIMAL \pm ***		
			TWO PLACE DECIMAL \pm ***		
			THREE PLACE DECIMAL \pm ***		



ADVANCED ACOUSTIC TECHNOLOGY CORPORATION