





1. SPECIFICATIONS

AMF-O60G42-3CWH2-IP67


01	Electret's Type	Foil type
02	Sensitivity	-42±3dB (0dB=1V/Pa,1KHz)
03	Standard Operation Voltage	2.0 V
04	Output Impedance	2.2 KΩ
05	Directivity	Omni directional
06	Frequency Range	100 - 10K Hz
07	Max. Operation Voltage	10V
08	Current Consumption	Max.0.5mA
09	Sensitivity Reduction	Within -3dB 0dB=1V/Pa,1KHz Vs=2.0to 1.5V
10	S/N Ratio	≥58dB
11	Sound Pressure Level	110 dB
12	Operating Temperature	-20~+60°C
13	Storage Temperature	-25~+70°C

REV NO.	REVISION NOTE	APPROVAL	DATE
---------	---------------	----------	------

White Waterproof Cloth (IP67)



Black Glue



Wire: UL1571,AWG30#
 Holder:DD-EQ-JTC70-06
 Connector:Equivalent to Molex 51021-0200

RoHS

TITLE: MICROPHONE		DRAWN: <i>Zack</i> 2018/05/09	SCALE: 5:1	SHEET: 1 of 1
PART NO. AMB-060G42-3CWH2-IP67		DESIGNED: R & D OF AAT	UNITS: mm	
DWG NO. B6022AL-SDN-D110-M	1 REV	CHECKED:	TOLERANCE ± 0.3	
		APPROVAL:	UNLESS OTHERWISE SPECIFIED:	
		MATERIAL: AL	ONE PLACE DECIMAL ± ***	
			TWO PLACE DECIMAL ± ***	
			THREE PLACE DECIMAL ± ***	



ADVANCED ACOUSTIC TECHNOLOGY CORPORATION