


1. SPECIFICATIONS

AMF-O60C42-NWH3-LF

01	Electret's Type	Foil type
02	Sensitivity	-42±3dB (0dB=1V/Pa,1KHz)
03	Standard Operation Voltage	2.0 V
04	Output Impedance	2.2 KΩ
05	Directivity	Omni directional
06	Frequency Range	100 - 10K Hz
07	Max. Operation Voltage	10V
08	Current Consumption	Max.0.5mA
09	Sensitivity Reduction	Within -3dB 0dB=1V/Pa,1KHz Vs=2.0to 1.5V
10	S/N Ratio	≥58dB
11	Sound Pressure Level	110 dB

REV NO.	REVISION NOTE	APPROVAL	DATE
---------	---------------	----------	------



Wire: UL1571,AWG30#
Connector:Molex 51021-0200
Holder:DD-EQ-JTC74-01

TITLE: MICROPHONE		DRAWN: <i>Moose</i> 2016/06/24	SCALE: 4:1	SHEET: 1 of 1
PART NO. AMF-060C42-NWH3-LF		DESIGNED: R & D OF AAT	UNITS: mm	
DWG NO. F6050AL-SB-D100-M11551		CHECKED:	TOLERANCE ± 0.2	
		APPROVAL:	UNLESS OTHERWISE SPECIFIED: ONE PLACE DECIMAL ± *** TWO PLACE DECIMAL ± *** THREE PLACE DECIMAL ± ***	
REV 2		MATERIAL: AL		



ADVANCED ACOUSTIC TECHNOLOGY CORPORATION