




## 1. SPECIFICATIONS

AMF-O60F38-CBH

01	Electret's Type	Foil type
02	Sensitivity	-38±3dB (0dB=1V/Pa,1KHz)
03	Standard Operation Voltage	2.0 V
04	Output Impedance	2.2 KΩ
05	Directivity	Omni directional
06	Frequency Range	100 - 20K Hz
07	Max. Operation Voltage	10V
08	Current Consumption	Max.0.5mA
09	Sensitivity Reduction	Within -3dB 0dB=1V/Pa,1KHz Vs=2.0to 1.5V
10	S/N Ratio	≥58dB
11	Sound Pressure Level	110 dB

REV NO.	REVISION NOTE	APPROVAL	DATE
---------	---------------	----------	------



HOLDER:DD-EQ-JTC70-06

RoHS

TITLE: <b>MICROPHONE</b>		DRAWN: <i>Jack</i> 2012/05/28	SCALE: 5:1	SHEET: 1 of 1
PART NO. <b>AMF-060F38-CBH</b>	<b>1</b> REV	DESIGNED: R & D OF AAT	UNITS: mm	
DWG NO. <b>F6027AP-SDN-M 9390</b>		CHECKED:	TOLERANCE $\pm 0.3$	
		APPROVAL:	UNLESS OTHERWISE SPECIFIED: ONE PLACE DECIMAL $\pm$ *** TWO PLACE DECIMAL $\pm$ *** THREE PLACE DECIMAL $\pm$ ***	
		MATERIAL: *****		



**ADVANCED ACOUSTIC TECHNOLOGY CORPORATION**