


## 1. SPECIFICATIONS

AMF-O60F42-CWH3

01	<b>Electret's Type</b>	Foil type
02	<b>Sensitivity</b>	-42±3dB (0dB=1V/Pa,1KHz)
03	<b>Standard Operation Voltage</b>	2.0 V
04	<b>Output Impedance</b>	2.2 KΩ
05	<b>Directivity</b>	Omni directional
06	<b>Frequency Range</b>	100 - 20K Hz
07	<b>Max. Operation Voltage</b>	10V
08	<b>Current Consumption</b>	Max.0.5mA
09	<b>Sensitivity Reduction</b>	Within -3dB 0dB=1V/Pa,1KHz Vs=2.0to 1.5V
10	<b>S/N Ratio</b>	≥58dB
11	<b>Sound Pressure Level</b>	110 dB

REV NO.	REVISION NOTE	APPROVAL	DATE
---------	---------------	----------	------



Wire: UL1571,32#AWG  
 Holder: HLM-JT-060.

RoHS

TITLE: MICROPHONE		DRAWN: Jack 2012/8/14	SCALE: 5:1	SHEET: 1 of 1
PART NO. AMF-060F42-CWH3	2 REV	DESIGNED: R & D OF AAT	UNITS: mm	
DWG NO. F6027AL-SDN-80-M		CHECKED:	TOLERANCE ± 0.3	
		APPROVAL:	UNLESS OTHERWISE SPECIFIED: ONE PLACE DECIMAL ± *** TWO PLACE DECIMAL ± *** THREE PLACE DECIMAL ± ***	
		MATERIAL: *****		



ADVANCED ACOUSTIC TECHNOLOGY CORPORATION