


1. SPECIFICATIONS





AMF-O60F42-DWH5

01	Electret's Type	Foil type
02	Sensitivity	-42±3dB (0dB=1V/Pa,1KHz)
03	Standard Operation Voltage	2.0 V
04	Output Impedance	2.2 KΩ
05	Directivity	Omni directional
06	Frequency Range	100 - 20K Hz
07	Max. Operation Voltage	10V
08	Current Consumption	Max.0.5mA
09	Sensitivity Reduction	Within -3dB 0dB=1V/Pa,1KHz Vs=2.0to 1.5V
10	S/N Ratio	≥58dB
11	Sound Pressure Level	110 dB

REV NO.	REVISION NOTE	APPROVAL	DATE
---------	---------------	----------	------



Wire:UL1571,30 AWG
 Connector : Equivalent to Molex51021-0200
 Holder:DD-EQ-JTC70-06



RoHS

TITLE: MICROPHONE		DRAWN: Moose 2016/11/25	SCALE: 5:1	SHEET: 1 of 1
PART NO. AMF-060F42-DWH5		DESIGNED: R & D OF AAT	UNITS: mm	
DWC NO. F6027AL-SBZ-D153-M 11675		CHECKED:	TOLERANCE ± 0.3	
		APPROVAL:	UNLESS OTHERWISE SPECIFIED: ONE PLACE DECIMAL ± *** TWO PLACE DECIMAL ± *** THREE PLACE DECIMAL ± ***	
REV		MATERIAL: AL		



ADVANCED ACOUSTIC TECHNOLOGY CORPORATION