



All dimensions are in mm

**Interface**

According to

RN\_108-01

**Documents**

PCB layout

MB\_926

T&R packaging

VG410.18500

**Material and plating**

**Connector parts**

- Center contact
- Outer contact (Interface)
- Outer contact (PCB)
- Dielectric
- Housing

**Material**

- Brass
- Bronze
- Zinc alloy
- LCP
- HTN

**Plating**

- AuroDur®, gold plated, 0.15  $\mu$ m
- Tin, min. 1.5  $\mu$ m
- Tin, min. 2  $\mu$ m

**Preliminary**

**Electrical data**

|                           |  |
|---------------------------|--|
| Impedance                 | 50 Ω   |
| Frequency                 | DC to 9 GHz  |
| Return loss               | ≥ 25 dB, DC to ≤ 3 GHz<br>≥ 20 dB, > 3 GHz to ≤ 6 GHz<br>≥ 12 dB, > 6 GHz to ≤ 9 GHz |
| Insertion loss            | ≤ 0.1 x √f(GHz) dB   |
| Insulation resistance     | ≥ 1x10 <sup>3</sup> MΩ   |
| Center contact resistance | ≤ 10 mΩ  |
| Outer contact resistance  | ≤ 5 mΩ   |
| Test voltage              | ≤ 800 V rms  |
| Working voltage           | ≤ 60 V rms   |
| Power current             | ≤ 1 A DC   |

– Connector only, VSWR in application depends decisive on PCB layout –

**Mechanical data**

|                       |         |
|-----------------------|---------|
| Mating cycles         | ≥ 25    |
| Engagement force      | ≤ 15 N* |
| Disengagement force   | ≥ 2 N   |
| Retention force latch | ≥ 110 N |
| Coding efficiency     | ≥ 150 N |
| Weight                | 1.97 g  |

**Preliminary**

\* according to USCAR 25 Rev. 3, tests specified in USCAR 17 Rev. 5 TG-G

**Environmental data**

|                                |   |
|--------------------------------|---|
| Temperature range              | -40 °C to +105 °C                               |
| Thermal shock                  | ISO 20860-2 clause 9.2                          |
| Temperature and humidity       | ISO 20860-2 clause 9.3                          |
| Vibration and mechanical shock | ISO 20860-2 clause 9.1                          |
| Dry heat                       | ISO 20860-2 clause 9.4                          |
| Soldering profile              | acc. to IEC 60068-2-58; Group 3 (250 °C / 30 s) |
| RoHS                           | compliant                                       |

**Packing**

|          |                        |
|----------|------------------------|
| Standard | 185 pcs in tape & reel |
|----------|------------------------|

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF\_35/09.14/6.2