


## ANT-PCB4242

### Features

- 800/900/1800/1900/2100MHz
- Omni Directional 1/2 Wave
- Miniature 42 x 42 x 1mm
- VSWR <3.0
- RG178 Coax 50Ω Impedance
- 2-3dBi Gain (nominal)
- Vertical Polarization
- Admitted Radiation Power 1W
- iPex/UFL Connector
- Operating temp -40 to +70°C




### Applications

- Embedded GSM Systems
- For World-wide Use


### Ordering Information

Part Number	Description
ANT-PCB4242-FL	Miniature PCB Penta Band Antenna


## Mechanical Detail



## Performance Data – TEST VSWR



## Performance Data – VSWR




## Performance Data – RETURN LOSS



## Performance Data—Smith Chart @ 880MHz

Far-field amplitude of gps+gsm01.nsi




Far-field amplitude, Eprincipal: Linear, Tau = 0.000 deg  
Gain = -8.33756 dBi  
Max far-field (global) = -34.95309 dB, Max far-field (plot) =  
-34.95309 dB  
Normalization: Reference, Network offset = 0.000 dB  
Hpeak at: 234.000 deg, Vpeak at: 0.000 deg  
Plot centering: on

NSI2000 V4.0.116, filename:c:\Documents and Settings\Administrator\  
Desktop\bill\gps+gsm01.nsi  
Measurement date/time: 11/26/2009 8:04:08 PM, Filetype: NSI-97  
Far-field Cut Analysis:  
Avg value: -9.754 dB  
-3. dB beam width: 41.64 deg  
-6. dB beam width: 59.14 deg  
-10. dB beam width: 78.02 deg  
Left sidelobe: -9.20 dB at -121.607 deg  
Right sidelobe: -2.13 dB at 167.933 deg  
Far-field display setup  
Azimuth (deg)  
Span = 360.00001 deg, Center = 180.00001 deg, #pts = 181  
Start = 0.000 deg, Stop = 360.00001 deg, Delta = 2.000 deg  
Elevation (deg)  
Center = 0.000 deg, #pts = 1

Selected beam(s) 1 of 9  
Beam Frequency Azimuth Elevation Pol  
1 0.880 GHz Azimuth Elevation Single-pol

## Performance Data—Smith Chart @ 920MHz

Far-field amplitude of gps+gsm01.nsi




Far-field amplitude, Eprincipal: Linear, Tau = 0.000 deg  
Gain = 1.08571 dBi  
Max far-field (global) = -33.66057 dB, Max far-field (plot) =  
-33.66056 dB  
Normalization: Reference, Network offset = 0.000 dB  
Hpeak at: 232.000 deg, Vpeak at: 0.000 deg  
Plot centering: on

NSI2000 V4.0.116, filename:c:\Documents and Settings\Administrator\  
Desktop\bill\gps+gsm01.nsi  
Measurement date/time: 11/26/2009 8:04:08 PM, Filetype: NSI-97  
Far-field Cut Analysis:  
Avg value: -6.232 dB  
-3. dB beam width: 51.85 deg  
-6. dB beam width: 73.16 deg  
-10. dB beam width: 105.26 deg  
Left sidelobe: -5.98 dB at -135.754 deg  
Right sidelobe: -4.99 dB at 173.967 deg  
Far-field display setup  
Azimuth (deg)  
Span = 360.00001 deg, Center = 180.00001 deg, #pts = 181  
Start = 0.000 deg, Stop = 360.00001 deg, Delta = 2.000 deg  
Elevation (deg)  
Center = 0.000 deg, #pts = 1

Selected beam(s) 1 of 9  
Beam Frequency Azimuth Elevation Pol  
2 0.920 GHz Azimuth Elevation Single-pol

## Performance Data—Smith Chart @ 960MHz

Far-field amplitude of gps+gsm01.nsi




```
Far-field amplitude, Eprincipal: Linear, Tau = 0.000 deg
Gain = -0.12529 dBi
Max far-field (global) = -35.22531 dB, Max far-field (plot) =
-35.22531 dB
Normalization: Reference, Network offset = 0.000 dB
Hpeak at: 208.000 deg, Vpeak at: 0.000 deg
Plot centering: on

-----
NSI2000 V4.0.116, Filename:C:\Documents and Settings\Administrator\
Desktop\bill\gps+gsm01.nsi
Measurement date/time: 11/26/2009 8:04:08 PM, Filetype: NSI-97
Far-field Cut Analysis:
Avg value: -7.296 dB
-3. dB beam width: 59.19 deg
-6. dB beam width: 93.33 deg
-10. dB beam width: 119.50 deg
Left Side-lobe: -2.66 dB at -139.777 deg
Right Side-lobe: -30.90 dB at 109.609 deg
Far-field display setup
Azimuth (deg)
Span = 360.00001 deg, Center = 180.00001 deg, #pts = 181
Start = 0.000 deg, Stop = 360.00001 deg, Delta = 2.000 deg
Elevation (deg)
Center = 0.000 deg, #pts = 1
Selected beam(s) 1 of 9
Beam Frequency Azimuth Elevation Pol
----
3 0.960 GHz Azimuth Elevation Single-pol
```

## Performance Data—Smith Chart @ 1710MHz


Far-field amplitude of gps+gsm01.nsi



```
Far-field amplitude, Eprincipal: Linear, Tau = 0.000 deg
Gain = -1.89386 dBi
Max far-field (global) = -41.61911 dB, Max far-field (plot) =
-41.61911 dB
Normalization: Reference, Network offset = 0.000 dB
Hpeak at: 309.99999 deg, Vpeak at: 0.000 deg
Plot centering: on

-----
NSI2000 V4.0.116, Filename:C:\Documents and Settings\Administrator\
Desktop\bill\gps+gsm01.nsi
Measurement date/time: 11/26/2009 8:04:08 PM, Filetype: NSI-97
Far-field Cut Analysis:
Avg value: -3.357 dB
-3. dB beam width: Not Found
-6. dB beam width: Not Found
-10. dB beam width: Not Found
Left Side-lobe: -1.21 dB at 35.196 deg
Right Side-lobe: Not Found
Far-field display setup
Azimuth (deg)
Span = 360.00001 deg, Center = 180.00001 deg, #pts = 181
Start = 0.000 deg, Stop = 360.00001 deg, Delta = 2.000 deg
Elevation (deg)
Center = 0.000 deg, #pts = 1
Selected beam(s) 1 of 9
Beam Frequency Azimuth Elevation Pol
----
4 1.710 GHz Azimuth Elevation Single-pol
```


## Performance Data—Smith Chart @ 1785MHz



Far-field amplitude, Spherical: Linear, Tau = 0.000 deg  
 Gain = 1.31446 dBi  
 Max far-field (global) = -40.52198 dB, Max far-field (plot) =  
 -41.522 dB  
 Normalization: Reference, Network offset = 0.000 dB  
 Mpeak at: 324.000 deg, Vpeak at: 0.000 deg  
 Plot centering: on

NSI2000 V4.0.116, Filename:C:\Documents and Settings\Administrator\  
 Desktop\bill\gps+gsm01.nsi  
 Measurement date/time: 11/26/2009 8:04:08 PM, Filetype: NSI-97  
 Far-field Cut Analysis:  
 Avg value: -3.945 dB  
 -3. dB beam width: 43.99 deg  
 -6. dB beam width: Not Found  
 -10. dB beam width: Not Found  
 Left Sidelobe: -1.26 dB at 17.095 deg  
 Right Sidelobe: Not Found  
 Far-field display setup  
 Azimuth (deg)  
 Span = 360.00001 deg, Center = 180.00001 deg, #pts = 181  
 Start = 0.000 deg, Stop = 360.00001 deg, Delta = 2.000 deg  
 Elevation (deg)  
 Center = 0.000 deg, #pts = 1  
 Selected beam(s) 1 of 9  
 Beam Frequency Azimuth Elevation Pol  
 ---  
 5 1.785 GHz Azimuth Elevation Single-pol


## Performance Data—Smith Chart @ 1850MHz



Far-field amplitude, Spherical: Linear, Tau = 0.000 deg  
 Gain = 0.97485 dBi  
 Max far-field (global) = -41.31947 dB, Max far-field (plot) =  
 -41.31947 dB  
 Normalization: Reference, Network offset = 0.000 dB  
 Mpeak at: 198.000 deg, Vpeak at: 0.000 deg  
 Plot centering: on

NSI2000 V4.0.116, Filename:C:\Documents and Settings\Administrator\  
 Desktop\bill\gps+gsm01.nsi  
 Measurement date/time: 11/26/2009 8:04:08 PM, Filetype: NSI-97  
 Far-field Cut Analysis:  
 Avg value: -41.319 dB  
 -3. dB beam width: 72.51 deg  
 -6. dB beam width: 86.92 deg  
 -10. dB beam width: 97.85 deg  
 Left Sidelobe: -11.50 dB at -65.475 deg  
 Right Sidelobe: -7.14 dB at 67.374 deg  
 Far-field display setup  
 Azimuth (deg)  
 Span = 360.00001 deg, Center = 180.00001 deg, #pts = 181  
 Start = 0.000 deg, Stop = 360.00001 deg, Delta = 2.000 deg  
 Elevation (deg)  
 Center = 0.000 deg, #pts = 1  
 Selected beam(s) 1 of 9  
 Beam Frequency Azimuth Elevation Pol  
 ---  
 6 1.850 GHz Azimuth Elevation Single-pol

## Performance Data—Smith Chart @ 1880MHz



## Performance Data—Smith Chart @ 1920MHz

