



### Overview

Lead time	Usually in Stock
-----------	------------------

### Main

Provided Equipment	User Manual USB cable
--------------------	--------------------------

### Physical

Height	1.50 in (3.8 cm)
Width	4.76 in (12.1 cm)
Depth	4.49 in (11.4 cm)
Net Weight	0.18 lb(US) (0.08 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

### Conformance

Standards	EN 55022 Class A EN 55024 ICES-003
Product Certifications	AS/NZS 3548 (C-Tick) Class A FCC part 15 class A GOST VCCI Class A

### Environmental

Ambient Air Temperature for Operation	32...113 °F (0...45 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	23...113 °F (-5...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Storage Relative Humidity	0...95 %

### Communications & Management

Authentication	Radius
----------------	--------

### Ordering and shipping details

GTIN	731304355533
------	--------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.01 in (5.1 cm)
Package 1 Width	6.26 in (15.9 cm)
Package 1 Length	9.25 in (23.5 cm)
Package 1 Weight	0.75 lb(US) (0.34 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------