


Notes:

1. Electrical Specifications:
Center Frequency = 1615 ±5 MHz.
Left Hand Circular Polarization.
2:1 VSWR BW. = 25 MHz Min.
Gain shall be 3dBic Min @ Zenith.
A/R shall be 3dB Max. @ Zenith.
Directivity in azimuth shall not vary by more than 3dB from Max. when measured at 25° elevation.
Directivity in elevation shall not vary by more than 5dB from zenith to 25° elevation.
Zin=50 Ohms.
2. 100% Electrical test prior to delivery.
3. Footprint and electrical specifications are subject to change.



08	REV NO	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED	 SPECTRUM CONTROL, INC.	
08	REV NO	DO NOT SCALE	DECIMAL .XX ± .02	DATE 5-24-10	FAIRVIEW
CN 54542-ENG	CHANGE NOTICE	THIRD ANGLE PROJECTION	DECIMAL .XXX ± .010	ENGR. J. KRAUS	PENNSYLVANIA
			ANGLES ± 0° 30'	DATE 5-24-10	DESCRIPTION:
			CODE IDENT. NUMBER 0LSFZ	SHEET 1 OF 1	ANTENNA w/ MAGNETS
					AR251615025CCLF