

## MHF4 Pigtail Cables

I-PEX MHF4 To SMA Female Bulkhead Jack 1.13 Coax Cable



### Applications

- SMA Female to MHF-4 jumper cable
- RF connections for radios and antennas
- MHF4 LK ideal for continuous shock & vibration applications

### Attenuation

Frequency (GHz)	1 GHz	2 GHz	3 GHz	4 GHz	5 GHz	6 GHz
dB 1/m	2.2	3.1	3.9	4.5	5.0	5.5

### Key Features

- Low Loss coaxial cable
- OD 1.13mm
- Color Grey
- Various cable lengths available
- RoHS and REACH compliant
- Crimp strength 20N minimum
- MHF4 locking solution available

### Electrical Specifications

Suggested working frequency:	0 to 6 GHz
Nominal Impedance:	50 +/- 3 Ω
Maximum operating voltage:	30 V
VSWR:	-15 dB (Max. between 0 and 6 GHz)

### Environmental Specifications


Operating Temperature:	-20 to +60 °C
Storage Temperature:	-20 to +60 °C
RoHS Compliant:	YES
REACH Compliant:	YES

## MHF4 Pigtail Cables


I-PEX MHF4 To SMA Female Bulkhead Jack 1.13 Coax Cable

### Mechanical Drawing


*Note: The O-ring is applicable to the IP67 models.*



#### RECOMMENDED MOUNTING HOLE



#### MHF 4L LK PLUG 3:1



#### MHF 4L PLUG 8:1

