Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

AX102906 Faceplates and Panels - KeyConnect Video F Coax, Surface



AX102906

Almond





For more Information please call

1-800-Belden1



General Description: KeyConnect Video F, Coax, Surface Usage (Overall) Suitable Applications: - Coax **Related Parts:** - Compatible KeyConnect-style Faceplate and Patch Panel **Physical Characteristics (Connectivity)** Capacity Access Front Connection: Flush Dimensions Dimensions: Height (mm) Width (mm) Depth (mm) 21.590 17.526 29.972 Materials Materials: **Description Material** Plastic - UL94V-0 Insert Color Almond Color: Weight Weight: 0.015 kg Packaging Packaging: 10 units packaged in a plastic bag. **Mechanical Characteristics (Connectivity)** Footprint/Type: KeyConnect 88.964 N Connector/Hardware Retention: Storage Temperature Range: -40°C To +70°C Installation Temperature Range: -10°C To +60°C -10°C To +60°C **Operating Temperature Range:** Applicable Specifications and Agency Compliance (Overall) **Applicable Standards & Environmental Programs** EU Directive 2002/95/EC (RoHS): Yes EU RoHS Compliance Date (mm/dd/yyyy): 07/01/2006 MII Order #39 (China RoHS): Yes Safety Listing: Bi-national Standard Listed Suitability Suitability - Indoor: Yes Transmission Characteristics (Connectivity) Notes (Overall) Notes: For proper installation refer to Installation Guide PX103826. Visit our web site at http://www.belden.com **Product Family** Part Numbers: Item Number Color

Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

AX102906 Faceplates and Panels - KeyConnect Video F Coax, Surface

AX102907	Elec. White
AX102908	Black
AX104567	lvory
AX105384	Dark Gray

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX102906	1 EA	0.015 KG			KCONN F-COAX MODULE ALM

Revision Number: 0 Revision Date: 08-14-2012

© 2017 Belden, Inc All Rights Reserved.

All Rights Reserved. Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information and belief at the date of its publication. The information provided in this Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in the ore that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.