

14.5 GHz Surface Mount Band pass Filter

B145LB1S

DESCRIPTION

One of DLI's surface mountable catalog bandpass filters. This filter utilizes DLI's low loss temperature stable materials which offer small size and minimal performance variation over temperature. The catalog BPF's are offered in a variety of frequency bands, which offers a drop in solution with highly repeatable performance.

FEATURES


- Small Size
- Fully Shielded Component
- Solder Surface Mount Package
- Moisture Sensitivity Level: MSL1
- Frequency Stable over Temperature
- Operating & Storage Temp: -55°C to +125°C
- Characteristic Impedance: 50Ω

SPECIFICATIONS*

Parameter	Frequency Range (GHz)	Min	Typ.	Max
Insertion Loss (dB)	14.1 - 14.9	2.75	3.0	3.5
Return Loss (dB)		10	14	-
Low Side Rejection (dB)	DC - 11.75	60	65	-
High Side Rejection (dB)	16.5 - 19.5	60	65	-
Input Power (W)				TBD
Size (L x W x H)	0.550 x 0.230 x 0.093 in 13.97 x 5.842 x 2.36 mm			

*Electrical specifications based on typical probed performance at room temperature. Insertion loss shall vary up to ±0.5dB over

Typical Measured Performance




14.5 GHz Surface Mount Band pass Filter

B145LB1S

Physical Dimensions

Units = inches



Recommended PCB Layout

