



B180-12D3



- Hybrid SAD-GDT Technology
- UL497B LISTED
- 20kA I_{max}
- 5kA I_{mp}
- 5kA I_n

	Electrical Characteristics																																											
 <p>G: 3-electrode gas tube R: Resistor D3: 3-pole clamping diode</p>	<table border="1"> <tr><td>Insertion loss</td><td></td><td>< 1 dB</td></tr> <tr><td>Protection mode(s)</td><td></td><td>Common/Differential mode</td></tr> <tr><td>DATA SPD TYPE</td><td></td><td>UL497B LISTED</td></tr> <tr><td>VOLTS</td><td>(V)</td><td>12</td></tr> <tr><td>WIRES</td><td></td><td>2W+GROUND</td></tr> <tr><td>LINE CURRENT MAX</td><td>(A)</td><td>0.3</td></tr> <tr><td>AMBIENT MIN</td><td>(C)</td><td>-50</td></tr> <tr><td>AMBIENT MAX</td><td>(C)</td><td>+85</td></tr> <tr><td>RESIDUAL VOLTAGE</td><td>(V)</td><td>30</td></tr> <tr><td>MCOV</td><td>(V)</td><td>15/72/72</td></tr> <tr><td>IN10 impulses 8/20µs</td><td>(kA)</td><td>5</td></tr> <tr><td>IMAX8/20µs</td><td>(kA)</td><td>20</td></tr> <tr><td>Iimp10/350µs</td><td>(kA)</td><td>5</td></tr> <tr><td>DATA SPEED</td><td>(bps)</td><td>10/100</td></tr> </table>		Insertion loss		< 1 dB	Protection mode(s)		Common/Differential mode	DATA SPD TYPE		UL497B LISTED	VOLTS	(V)	12	WIRES		2W+GROUND	LINE CURRENT MAX	(A)	0.3	AMBIENT MIN	(C)	-50	AMBIENT MAX	(C)	+85	RESIDUAL VOLTAGE	(V)	30	MCOV	(V)	15/72/72	IN10 impulses 8/20µs	(kA)	5	IMAX8/20µs	(kA)	20	Iimp10/350µs	(kA)	5	DATA SPEED	(bps)	10/100
Insertion loss		< 1 dB																																										
Protection mode(s)		Common/Differential mode																																										
DATA SPD TYPE		UL497B LISTED																																										
VOLTS	(V)	12																																										
WIRES		2W+GROUND																																										
LINE CURRENT MAX	(A)	0.3																																										
AMBIENT MIN	(C)	-50																																										
AMBIENT MAX	(C)	+85																																										
RESIDUAL VOLTAGE	(V)	30																																										
MCOV	(V)	15/72/72																																										
IN10 impulses 8/20µs	(kA)	5																																										
IMAX8/20µs	(kA)	20																																										
Iimp10/350µs	(kA)	5																																										
DATA SPEED	(bps)	10/100																																										
Mechanical Characteristics																																												
<table border="1"> <tr><td>TECHNOLOGY</td><td>SAD-GDT</td></tr> <tr><td>NETWORK CONFIGURATION</td><td>2W+G</td></tr> <tr><td>CONNECTION METHOD</td><td>Screw Terminal (16-22AWG)</td></tr> <tr><td>MOUNTING</td><td>DIN RAIL</td></tr> <tr><td>MATERIAL</td><td>Thermoplastic UL94-V0</td></tr> <tr><td>NEMA RATING (IP RATING)</td><td>NEMA 2 (IP20)</td></tr> <tr><td>DIMENSIONS</td><td>See diagram</td></tr> <tr><td>WEIGHT</td><td>0.30 lbs</td></tr> <tr><td>SPARE PART</td><td>n/a</td></tr> </table>		TECHNOLOGY	SAD-GDT	NETWORK CONFIGURATION	2W+G	CONNECTION METHOD	Screw Terminal (16-22AWG)	MOUNTING	DIN RAIL	MATERIAL	Thermoplastic UL94-V0	NEMA RATING (IP RATING)	NEMA 2 (IP20)	DIMENSIONS	See diagram	WEIGHT	0.30 lbs	SPARE PART	n/a																									
TECHNOLOGY	SAD-GDT																																											
NETWORK CONFIGURATION	2W+G																																											
CONNECTION METHOD	Screw Terminal (16-22AWG)																																											
MOUNTING	DIN RAIL																																											
MATERIAL	Thermoplastic UL94-V0																																											
NEMA RATING (IP RATING)	NEMA 2 (IP20)																																											
DIMENSIONS	See diagram																																											
WEIGHT	0.30 lbs																																											
SPARE PART	n/a																																											
Standards																																												
<table border="1"> <tr><td>Certification</td><td>UL 497B</td></tr> <tr><td>UL STANDARD</td><td>UL497B</td></tr> <tr><td>UL CATEGORY</td><td>QVGQ</td></tr> <tr><td>UL FILE NUMBER</td><td>E184939</td></tr> <tr><td>STANDARDS</td><td>IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993</td></tr> <tr><td>ENVIRONMENTAL STANDARDS</td><td>ROHS</td></tr> </table>		Certification	UL 497B	UL STANDARD	UL497B	UL CATEGORY	QVGQ	UL FILE NUMBER	E184939	STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS	ROHS																															
Certification	UL 497B																																											
UL STANDARD	UL497B																																											
UL CATEGORY	QVGQ																																											
UL FILE NUMBER	E184939																																											
STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993																																											
ENVIRONMENTAL STANDARDS	ROHS																																											
Part number																																												
510202																																												

