



## **Surge arrester**

3-electrode arrester

**Series/Type:** T2ES-A350X  
**Ordering code:** B88069X4260B502  
Version/Date: Issue 05 / 2010-08-30

**Features**

- Standard size
- Very fast response time
- Very high current rating
- Stable performance over life
- Very low capacitance
- High insulation resistance
- RoHS-compatible

**Applications**

- Branch exchange (MDF)
- Line protection
- Station protection

**Electrical specifications**

DC spark-over voltage <sup>1) 2) 4)</sup>	350 ... 550	V
Impulse spark-over voltage <sup>4)</sup>		
at 100 V/ $\mu$ s - for 99 % of measured values	< 580	V
- typical values of distribution	< 500	V
at 1 kV/ $\mu$ s - for 99 % of measured values	< 660	V
- typical values of distribution	< 570	V
Service life		
10 operations      50 Hz; 1 s <sup>5)</sup>	10	A
1 operation      50 Hz; 0.18 s (9 cycles) <sup>5)</sup>	50	A
100 operations    8/20 $\mu$ s <sup>6)</sup>	3	kA
10 operations    8/20 $\mu$ s <sup>5)</sup>	10	kA
1 operation      8/20 $\mu$ s <sup>5)</sup>	25	kA
Insulation resistance at 100 V <sub>DC</sub> <sup>4)</sup>	> 10	G $\Omega$
Capacitance at 1 MHz <sup>4)</sup>	< 1.5	pF
Transverse delay time <sup>3)</sup>	< 0.2	$\mu$ s
Arc voltage at 1 A	~ 35	V
Glow to arc transition current	~ 1	A
Glow voltage	~ 200	V
Weight	~ 2	g
Operation and storage temperature	-40 ... +90	°C
Climatic category (IEC 60068-1)	40/ 90/ 21	
Marking, blue negative	<b>EPCOS</b> <b>350 YY O</b> 350 - Nominal voltage YY - Year of production O - Non radioactive	

<sup>1)</sup> At delivery AQL 0.65 level II, DIN ISO 2859

<sup>2)</sup> In ionized mode

<sup>3)</sup> Test according to ITU-T Rec. K.12

<sup>4)</sup> Tip or ring electrode to center electrode

<sup>5)</sup> Total current through center electrode, half value through tip respectively ring electrode.

<sup>6)</sup> Total current through center electrode, same value through tip respectively ring electrode.

Terms in accordance with ITU-T Rec. K.12 and DIN 57845/VDE0845