


# BK1100FHU

High temperature & long life type



## ■ Dimensions (with tube)



Battery performance and cycle life are strongly affected by how they are used. In order to maximize battery safety, please consult Panasonic when determining charge/discharge specs, warning label contents and unit design.

## ■ Specifications

Diameter		33.0 +0 / -1.0 mm
Height		91.0 +0 / -1.5 mm
Approximate Weight		300g
Nominal Voltage		1.2V
Discharge*1 Capacity	Average*2	11300 mAh
	Rated (min.)	11000 mAh
Approx. Internal Impedance at 1000Hz at charged state.		5 mΩ
Charge	Standard	1100 mA X 16 hrs.
	Rapid*3	5500 mAh X 2.4 hrs.
	Low rate	550 mA X 32 hrs. 367 mA X 48 hrs.
Ambient Temperature	Charge	Low rate
	Standard	-30 °C to 75 °C
	Rapid	-30 °C to 60 °C
Discharge		-40 °C to 85 °C
Storage	<1 year	-20 °C to 35 °C
	<6 months	-20 °C to 45 °C
	<1 month	-20 °C to 55 °C
	<1 week	-20 °C to 65 °C

\*1 After charging at 0.1 It for 16 hours, discharging at 0.2 It

\*2 For reference only.

\*3 Need specially designed control system. Please contact Panasonic for details.

\*The data in this document are for descriptive purposes only and are not intended to make or imply any guarantee or warranty.